



TABELA DE PREÇOS

é[®] SISTEMAS
VISUAL COMMUNICATION SOLUTIONS
MULTIMEDIA PRODUCTS



AMC

IMAGEM	REF.MODELO / CARACTERISTICAS	UNID.	€ PVPR	€ PVPR C/IVA
--------	------------------------------	-------	--------	--------------

EN 54-24 Ceiling Loudspeakers

	AMC-EVAC5EN EN 54-24 ceiling 5" loudspeaker with fire dome. Power: 6W, Transformer power taps: 100V/6W-3W-1.5W 0.75W-0.25W, Frequency response: 180-17'500 Hz, Sensitivity: 87 dB (1 W/1 m). Dimensões: 19x9,4cm, Material: Steel, Cor: White (RAL 9016)	Unid.	45,99	56,57
	AMC-MC4EN EN54-24 metal ceiling 4" loudspeaker with metal grill and plastic dome. Equipped with ceramic wire terminal and thermal fuse. Quick fit mount and built-in line transformer, 100V/6W-3W-1.5W, Frequency response: 110-15'000Hz, Cor: White (RAL 9016)	Unid.	26,35	32,41

EN 54-24 Sound projectors

	AMC-SP10EN EN 54-24 5" sound projector. Power: 10 W, Transformer power taps: 100V/10W-5W-2.5W-1.25W, Frequency response: 120- 18'000 Hz, Sensitivity: 90 dB (1 W/1 m), Dimensions: 13,8x20,4cm Material: Plastic housing with stainless steel bracket & hardware, Cor: White (RAL 9016)	Unid.	78,58	96,65
---	--	-------	-------	-------

EN 54-24 Horn Loudspeakers

	AMC-HQ10EN EN 54-24 horn loudspeaker. Power: 10 W, Transformer power taps: 100V/10W-5W-2.5W-1.25W Frequency response: 340- 16'000 Hz, Sensitivity: 105 dB (1 W/1 m), Dimensions: 17x13x23cm Material: Plastic housing with stainless steel bracket & hardware, Colour: RAL 9016	Unid.	78,12	96,08
---	---	-------	-------	-------

IMAGEM	REF.MODELO / CARACTERISTICAS	UNID.	€ PVPR	€ PVPR C/IVA
--------	------------------------------	-------	--------	--------------

Powered Cabinet Loudspeakers

	AMC-POWERBOX5HP Powered stereo speaker system with IR remote control, 5" woofer and 1" tweeter, wall mount bracket included. System consists of one active loudspeaker with built-in stereo amplifier and one passive speaker. Rated power 2x20W, 115-20'000Hz, Cor Branca (RAL 9003)	Par	201,07	247,31
	AMC-POWERBOX5W Coluna profissional 1-Via, 5,25" activas, amplificada, potência 2x20W 80Hz-20'000Hz, Inclui suporte de parede, Cor Branca (RAL 9016).	Par	136,36	167,72
	AMC-POWERBOX5B Coluna profissional 1-Via, 5,25" activas, amplificada, potência 2x20W 80Hz-20'000Hz, Inclui suporte de parede, Cor Preta (RAL 9017).	Par	136,36	167,72

Cabinet Loudspeakers

	AMC-VIVA4W Wall mount 2-way loudspeaker, 4" Woofer and 1" tweeter, wall mount bracket included, 20W/8Ω, 100V/20W-10W-5W-2,5W-8Ω, 90-20'000Hz, White color (RAL 9016)	Unid.	57,58	71,07
	AMC-VIVA4B Wall mount 2-way loudspeaker, 4" Woofer and 1" tweeter, wall mount bracket included, 20W/8Ω, 100V/20W-10W-5W-2,5W-8Ω, 90-20'000Hz, Black color (RAL 9017)	Unid.	57,58	71,07
	AMC-VIVA5W Colunas de Parede 2-Vias com 5" Woofer/ 1" tweeter. Suporte parede incluido, 30W/8 Ohms, 100V/25W-15W-10W-5W 8Ohms, 80-20'000Hz, Cor Branca (RAL 9016)	Unid.	61,71	75,90
	AMC-VIVA5B Colunas de Parede 2-Vias com 5" Woofer/ 1" tweeter. Suporte parede incluido, 30W/8 Ohms, 100V/25W-15W-10W-5W 8Ohms, 80-20'000Hz, Cor Preta (RAL 9017)	Unid.	61,71	75,90
	AMC-VIVA8W Colunas de Parede 2-Vias com 8" Woofer/ 1" tweeter. Suporte parede incluido, 60W/8Ohms, 100V/50W-25W-12,5W-6W-3W 8Ohms, 60-20'000Hz, Cor Branca (RAL 9016)	Unid.	145,60	179,09
	AMC-VIVA8B Colunas de Parede 2-Vias com 8" Woofer/ 1" tweeter. Suporte parede incluido, 60W/8Ohms, 100V/50W-25W-12,5W-6W-3W 8Ohms, 60-20'000Hz, Cor Preta (RAL 9017)	Unid.	145,60	179,09

IMAGEM	REF.MODELO / CARACTERISTICAS	UNID.	€ PVPR	€ PVPR C/IVA
Cabinet Loudspeakers				
	AMC-iPlay4WT Colunas de Parede 2-Vias com 4" Woofer/ 1" tweeter, transformador interno e suporte parede incluido, 30W/8 Ohms, 100V/16W-8W-4W-2W 8Ohms, 110-20'000Hz, Cor Branca (RAL 9018)	Unid.	38,13	46,90
	AMC-iPlay4BT Colunas de Parede 2-Vias com 4" Woofer/ 1" tweeter, transformador interno e suporte parede incluido, 30W/8 Ohms, 100V/16W-8W-4W-2W 8Ohms, 110-20'000Hz, Cor Preta (RAL 9017) 	Unid.	38,13	46,90
	AMC-iPlay5WT Colunas de Parede 2-Vias com 5" Woofer/ 1" tweeter, transformador interno e suporte parede incluido,35W/8 Ohms, 100V/30W-16W-8W-4W 8Ohms, 120-20'000Hz, Cor Branca (RAL 9018)	Unid.	50,84	62,54
	AMC-iPlay5BT Colunas de Parede 2-Vias com 5" Woofer/ 1" tweeter, transformador interno e suporte parede incluido, 35W/8 Ohms, 100V/30W-16W-8W-4W 8Ohms, 120-20'000Hz, Cor Preta (RAL 9017)	Unid.	50,84	62,54
	AMC-iPlay6W Colunas de Parede 2-Vias com 6" Woofer/ 1,5" tweeter, inclui suporte de parede, 90W/8 Ohms, 70-20'000Hz, Cor Branca (RAL 9018) 	Unid.	80,89	99,49
	AMC-iPlay6B Colunas de Parede 2-Vias com 6" Woofer/1,5" tweeter,inclui suporte de parede, 90W/8 Ohms, 70-20'000Hz, Cor Preta (RAL 9017)	Unid.	80,89	99,49
	AMC-VIVA3-302WT Colunas de Parede 2-Vias com 3" Woofer/ 1" tweeter, transformador interno e suporte parede incluido, 25W/8 Ohms, 100V/15W-7.5W-3W 8Ohms, 150-20'000Hz, Cor Branca (RAL9016) 	Unid.	33,97	41,79
	AMC-VIVA3-302BT Colunas de Parede 2-Vias com 3" Woofer/ 1" tweeter, transformador interno e suporte parede incluido, 25W/8 Ohms, 100V/15W-7.5W-3W 8Ohms,150-20'000Hz, Cor Preta (RAL 9017)	Unid.	33,97	41,79
	AMC-VIVA3-502WT Colunas de Parede 2-Vias com 5" Woofer/ 1" tweeter, transformador interno e suporte parede incluido, 50W/8 Ohms, 100V/25W-15W-5W 8Ohms, 110-20'000Hz, Cor Branca (RAL 9016)	Unid.	57,32	70,50
	AMC-VIVA3-502BT Colunas de Parede 2-Vias com 5" Woofer/ 1" tweeter, transformador interno e suporte parede incluido, 50W/8 Ohms, 100V/25W-15W-5W 8Ohms, 110-20'000Hz, Cor Preta (RAL 9017)	Unid.	57,32	70,50
	AMC-EVACW5 Colunas de Parede de metal com 5" speaker e transformador interno 100V, 100V/4 W-2 W-1 W-0,5 W-0,25 W, 150-20'000Hz, Cor Branca Papyrus (RAL 9018)	Unid.	36,05	44,35
	AMC-iSpeak6W Colunas de Parede com 5.5" speaker e transformador interno, 100V/6W- 3W, 130-17'000Hz, Cor Branca (RAL 9016)	Unid.	21,96	27,01
	AMC-iSpeak6WP Colunas de Parede com 5.5" speaker e transformador interno, 100V/6W- 3W, 130-17'000Hz, Cor Branca Papyrus (RAL 9018)	Unid.	21,96	27,01
	AMC-PS6 Surface mount loudspeaker with 6" speaker and built-in line transformer, 100V/10W-5W-2.5W, 80-18'000Hz, White color (RAL 9016) 	Unid.	28,43	34,96
	AMC-W3 Colunas de Parede com 4" speaker transformador interno, 100V/3W-1.5W-0.75W, 200-15'000Hz, Cor Branca (RAL 9016)	Unid.	15,48	19,05
	AMC-W10 Colunas de Parede com 4" speaker transformador interno, 100V/10W-5W-2.5W, 200-15'000Hz, Cor Branca (RAL 9016)	Unid.	16,64	20,47
	AMC-W10RS Colunas de Parede com 4" speaker transformador interno, 100V/10W-5W-2.5W, 180-15'000Hz, Cor Branca Papyrus (RAL 9018)	Unid.	25,19	30,99

IMAGEM	REF.MODELO / CARACTERISTICAS	UNID.	€ PVPR	€ PVPR C/IVA
--------	------------------------------	-------	--------	--------------

Ceiling Loudspeakers

	AMC-EVAC50X Coluna de embutir em metal, 5" loudspeaker com caixa em metal Anti-Fogo, transformador interno, 100V/6W-3W-1W-0.75W, 150-18'000Hz, Cor Branca (RAL 9016) 	Unid.	36,98	45,48
	AMC-EVAC5 Coluna de embutir em metal, 5" loudspeaker com caixa em metal Anti-Fogo, transformador interno, 100V/6W-3W-1W-0.75W-0.25W, 240-20'000Hz, Cor Branca (RAL 9016)	Unid.	53,16	65,38
	AMC-EVAC6 Coluna de embutir em metal, 6" loudspeaker com caixa em metal Anti-Fogo, transformador interno, 100V/10W-5W-2.5W, 150-20'000Hz, Cor Branca (RAL 9016) 	Unid.	45,07	55,43
	AMC-MC4TA Coluna de embutir em metal, 4" loudspeaker com grelha metálica e transformador interno, 100V/6W-3W-1.5W, 110-17'000Hz, Cor Branca (RAL 9016)	Unid.	12,48	15,35
	AMC-MC5T Metal ceiling 5" loudspeaker with metal grill,quick fit mount and built-in line transformer, 100V/10W-5W-2.5W, 110-17'000Hz, White color (RAL 9016)	Unid.	18,72	23,03
	AMC-MC6T Metal ceiling 6" loudspeaker with metal grill,quick fit mount and built-in line transformer, 100V/6W-3W, 100-18'000Hz, White color (RAL 9016)	Unid.	14,56	17,91
	AMC-PC3 Coluna de embutir em plástico duplo cone 3" loudspeaker com grelha metálica e transformador interno, 100V/6W-3W-1.5W, 150-20'000Hz, Cor Branca (RAL 9016) 	Unid.	13,64	16,77
	AMC-PC4HP Coluna de embutir em plástico 4" loudspeaker com grelha metálica e transformador interno, 40W/8Ohms, 100V/20W-12W-8W-4W-2W 8Ohms, 150-20'000Hz, Cor Branca (RAL 9016)	Unid.	64,71	79,59
	AMC-PC5T Coluna de embutir em plástico 5" loudspeaker com grelha metálica e transformador interno,100V/10W-5W-2.5W-1.25W, 90-20'000Hz, Cor Branca (RAL 9016)	Unid.	20,57	25,30
	AMC-PC5TX Coluna de embutir em plástico 5" loudspeaker com grelha metálica e transformador interno,100V/10W-5W-2.5W-1.25W, 100-20'000Hz, Cor Branca (RAL 9016) 	Unid.	21,96	27,01
	AMC-PC6T Plastic full range 6" loudspeaker with metal grill, quick fit mount and built-in line transformer, 100V 6W-3W, 100-15'000Hz, White color (RAL 9016)	Unid.	14,33	17,62
	AMC-PC8T Coluna de embutir em plástico 8" loudspeaker com grelha metálica e transformador interno, 100V/20W-10W-5W-2.5W, 80-20'000Hz, Cor Branca (RAL 9016)	Unid.	28,89	35,53
	AMC-PC8TX Coluna de embutir em plástico 8" loudspeaker com grelha metálica e transformador interno, 100V/20W-10W-5W-2.5W, 60-20'000Hz, Cor Branca (RAL 9016) 	Unid.	31,66	38,94

Ceiling Loudspeakers Low Impedance

	AMC-PC6 Coluna de tecto de embutir, 6.5" loudspeaker com grelha metálica, 50W/8 Ohms, 80-20'000Hz, Cor Branca 	Unid.	25,42	31,27
	AMC-PC6HP Rimless high performance coaxial 6.5" ceiling loudspeaker with stell grill, quick fit mount, 35W/8Ω, 75-20'000Hz, White color RAL (9003) 	Unid.	62,40	76,75
	AMC-PC5X Coluna de tecto de embutir em plástico, 5" loudspeaker com grelha metálica, 20W/8 Ohms, 100-20'000Hz, Cor Branca 	Unid.	18,03	22,17
	AMC-PC8X Coluna de tecto de embutir em plástico, 8" loudspeaker com grelha metálica, 40W/8 Ohms, 50-20'000Hz, Cor Branca 	Unid.	28,43	34,96

Waterproof Loudspeakers

NEW 	AMC-WP5 Waterproofness coaxial 5" low impedance ceiling loudspeaker. Plastic speaker membrane, moisture isolated magnet and speaker coil. 40W/4Ω, 80-20'000Hz, White color RAL (9016)	Unid.	18,49	22,74
NEW 	AMC-WP6 Waterproofness coaxial 6" low impedance ceiling loudspeaker. Plastic speaker membrane, moisture isolated magnet and speaker coil. 50W/4Ω, 70-20'000Hz, White color RAL (9016)	Unid.	20,80	25,58

IMAGEM	REF.MODELO / CARACTERISTICAS	UNID.	€ PVPR	€ PVPR C/IVA
--------	------------------------------	-------	--------	--------------

Professional Loudspeakers

	AMC-POWERBOXD12 Coluna profissional 2-Vias, 12" activas, amplificador classe D, 150W RMS 60-20'000KHz, Cor Preta (RAL 9017)	Unid.	321,24	395,13
	AMC-MUSICBOXD12 Coluna profissional 2-Vias, 12" activas. Já com USB, SD/MMC Player e controlo remoto. RMS 150W. 45-20'000KHz, Cor Preta (RAL 9017)	Unid.	367,47	451,98
	AMC-SPEAKERBOXD12 Coluna profissional 2-Vias, 12" passivas, potência saída 230W (8 Ohms), 50-18'000KHz, Cor Preta (RAL 9017)	Unid.	270,40	332,59

Horn Loudspeakers (Colunas tipo Corneta)

	AMC-MHQ60X Music quality weatherproof 2-way ABS plastic horn loudspeaker with built-in line transformer, IP66, 100V/ 60W-30W-15W, 98-18 000Hz, Light Grey color (RAL 7035)	Unid.	210,31	258,68
	AMC-MH50 Coluna Corneta à prova de água, 2-vias com transformador incluído, 50W/8 Ohms IP55, 100V/ 50W-25W-12,5W-8 Ohms, 90-20 000Hz, Cold Grey color (RAL 7035)	Unid.	145,60	179,09
	AMC-HQ10 Coluna Corneta à prova de água, com transformador incluído, IP65 , 100V/10W- 7.5W-5W, 400-10KHz, Cor Branca (RAL9018)	Unid.	29,81	36,67
	AMC-HQ15 Coluna Corneta à prova de água, com transformador incluído, IP66 , 100V/15W- 7.5W, 400-5000Hz, Cor Branca	Unid.	33,44	42,36
	AMC-HQ30 Coluna Corneta à prova de água, com transformador incluído, IP66 , 100V/30W- 15W, 400-6000Hz, Cor Branca	Unid.	53,16	65,38
	AMC-H15 Coluna Corneta à prova de água, com transformador incluído, IP65 , 100V/15W- 10W-5W-3W, 400-8000Hz, Cor Branca (RAL9018)	Unid.	52,92	65,10

Sound Projectors (Colunas tipo projetor de som)

	AMC-SPM10HP Projector de som com transformador interno e caixa em alumínio, IP66, 100V/10W-5W-2.5W-1.25W, 130-20,000Hz, Cor Branca (RAL9016)	Unid.	108,62	133,61
	AMC-SPM20HP Projector de som com transformador interno e caixa em alumínio, IP66, 100V/20W-10W-5W-8Ω, Cor Branca (RAL9016)	Unid.	123,64	152,08
	AMC-SP10 Projector de som, caixa em ABS com transformador interno, IP55, 100V/10W-5W-2.5W, 130-15'000Hz, Dimensões: ø138mm x 205mm Cor Branca (RAL9016) ou Preta (RAL9017)	Unid.	38,60	47,47
	AMC-SPM20 Projector de som, caixa em alumínio com transformador interno, IP55, 100V/20W- 10W-5W, 130-15'000Hz, Cor Branca Papyrus (RAL9018)	Unid.	57,78	71,07
	AMC-SPMB10 Projector de som bidirecional, caixa em alumínio com transformador interno, IP55, 100V/10W 5W-2,5W, 130-15'000Hz, Cor Branca Papyrus (RAL9018)	Unid.	67,02	82,44

Subwoofers

	AMC-SUB2 Subwoofer Activo 10" , 200W, 20-130Hz, Cor Preta (RAL9017)	Unid.	355,91	437,77
	AMC-SUB100V Passive subwoofer for 100V or low impedance background music systems. 8" woofer, low pass filter, 100V line power selector and low impedance input. 100V/60W-30W-15W-7,5W -8Ω, 40- 1000Hz. White color RAL (9016)	Unid.	228,80	281,42

IMAGEM	REF.MODELO / CARACTERISTICAS	UNID.	€ PVPR	€ PVPR C/IVA
--------	------------------------------	-------	--------	--------------

Spherical Loudspeakers (Colunas esféricas)

	AMC-SL30 Coluna esférica 6.5" woofer/ 1" tweeter e transformador interno, 100V/30W-15W-7,5W-3,75W, 100-20'000KHz, Cor branca (RAL9016) ou Cor Preta (RAL9017)	Unid.	86,67	106,60
	AMC-SL20M Coluna esférica 2-vias com 6" woofer/ 1" tweeter e transformador interno, 100V/20W-10W-5W, 180-20'000KHz, Cor branca (RAL9016) ou Cor Preta (RAL9017)  Em Stock	Unid.	68,87	84,71

Column Loudspeakers (Colunas em Coluna)


	AMC-COM20HP Coluna em alumínio de 2-vias com 4x3.5" woofer / 0,8" tweeter com transformador incluído, 100V/20W-10W-5W-2.5W, 120-20000Hz, IP66, Cor Branca (RAL 9016)	Unid.	196,44	241,63
	AMC-COM30HP Coluna em alumínio de 2-vias com 6x3.5" woofer / 0,8" tweeter com transformador incluído, 100V/30W-15W-7,5W-3,75W, 110-20000Hz, IP66, Cor Branca (RAL 9016)	Unid.	256,53	315,54
	AMC-COM320 Coluna em alumínio de 2-vias com 2x3" woofer / 1" tweeter com transformador incluído, 100V/20W-10W, 135-20000Hz, IP66, Cor Branca (RAL 9016)	Unid.	78,58	96,65
	AMC-COM340 Coluna em alumínio de 2-vias com 4x3" woofer / 1" tweeter com transformador incluído, 100V/40W-20W, 135-20000Hz, IP66, Cor Branca (RAL 9016)	Unid.	120,18	147,82
	AMC-COM420 Coluna em alumínio de 2-vias com 2x4" woofer / 1" tweeter com transformador incluído, 100V/20W-10W, 120-20000Hz, IP66, Cor Branca (RAL 9016)	Unid.	104,00	127,92
	AMC-COM440 Coluna em alumínio de 2-vias com 4x4" woofer / 1" tweeter com transformador incluído, 100V/40W-20W, 120-20000Hz, IP66, Cor Branca (RAL 9016)	Unid.	147,91	181,93
	AMC-COM20 Coluna em metal com 2x5" speakers, transformador incluído, IP54, 100V/20W-10W, 100-15000Hz, Cor Cinza (RAL 9007)	Unid.	64,71	79,59
	AMC-COM40 Coluna em metal com 4x5" speakers, transformador incluído, IP54, 100V/40W-20W, 100-15000Hz, Cor Cinza (RAL 9007)	Unid.	83,20	102,34
	AMC-COMSLIM30 Coluna em alumínio com 4x2" woofers e 1x1" tweeter, transformador incluído 100V, 30W-15W-7.5W-8Ω, 180-18'000Hz, IP55, Cor Branca (RAL 9016)	Unid.	78,58	96,65

Music Players


	AMC-MP01 Music player MP 01 com CD Player, Rádio FM e leitor cartões flash, 2 saídas de áudio XLR independentes para CD e FM Radio	Unid.	432,18	531,58
	AMC-MP02 Music player MP 02 com CD Player, Rádio AM/FM e leitor cartões flash MP 02 tem 1 saída de áudio RCA para CD e Rádio  Em Stock	Unid.	427,56	525,89
	AMC-MP02B Music player MP 02B com CD Player, Rádio AM/FM, leitor cartões flash e interface Bluetooth. 1 saída de áudio RCA	Unid.	473,78	582,75
	AMC-MP03 Music player MP03 com CD Player, Rádio FM e Leitor cartões flash e função RS232, Saída de áudio RCA e terminal Phoenix para CD e FM tuner.	Unid.	464,53	571,38

IMAGEM	REF.MODELO / CARACTERISTICAS	UNID.	€ PVPR	€ PVPR C/IVA
--------	------------------------------	-------	--------	--------------

Music Players

	AMC-MP05 Music player MP05 com CD Player, Leitor cartões (Flash Disc e SD MMC). Porta RS232.	Unid.	418,31	514,52
	AMC-MP06S Music player MP 06S with Speed control for CD, USB,MMC cards. Player has integrated FM tuner with 30 radio station pre-sets. IR remote control included. Two separate CD, SD, USB and FM tuner RCA line outputs. Priority output for nonstop audio.	Unid.	496,89	611,17
	AMC-LiveRadio Rádio Internet com leitor de cartões (Flash Disc e SD), Rádio FM e Media PLayer. WI-FI e LAN para acesso à internet. Saida RCA e S/PDIF.	Unid.	446,04	548,63

Professional Power Amplifiers

	AMC-A100 Amplificador Stereo, 2x70W 8 Ohms, 2x100W 4Ohms. Dimensões 45x482x320mm, Peso 8kg	Unid.	247,29	304,17
	AMC-A200 Amplificador Stereo, 2x130W 8 Ohms, 2x200W 4Ohms. Dimensões 45x482x320mm, Peso 8,3kg	Unid.	284,27	349,65
	AMC-2A400 Amplificador Stereo, 2x400W 8 Ohms, 2x700W 4Ohms. Dimensões 89x482x453mm, Peso 23kg	Unid.	529,24	650,97
	AMC-2A600 Amplificador Stereo, 2x600W 8 Ohms, 2x1050W 4Ohms. Dimensões 89x482x453mm, Peso 25kg	Unid.	596,27	733,41

Mixing Preamplifiers

	AMC-iMIX63 Mixer preamplifier com 6 universal combi XLR e 3x stereo RCA com XLR stereo balanceado, stereo RCA e 2x6,3mm TRS jack. Phantom power	Unid.	203,38	250,15
	AMC-iMIX2 Zone mixer, 4 LINE/MIC e 2xRCA LINE inputs, 2xStereo balanced outputs, RS-232 control	Unid.	312,00	383,76

Digital Signal Processors

	AMC-DSP88 Matriz digital DSP88 com 8 entradas e 8 saídas com MIC/LINE.Entrada audio balanceada e Phantom power. Ethernet, USB e RS232.	Unid.	1.594,67	1.961,44
--	--	-------	----------	----------

Mixing Amplifiers

	AMC-MA2X100 Amplificador Mix, 3x MIC, 1x CD, 1x AUX, 1x TAPE, 2x LINE outputs, 100+100W RMS	Unid.	335,11	412,19
	AMC-ICOM2X20 Mini Amplificador, 2 Canais (D Class), 1x MIC, 1x LINE para cada canal, 20W+20W RMS 4 Ohms	Unid.	154,84	190,46
	AMC-ICOMC2X20 Small size D-class stereo amplifier. 2x20W power. RS232 control interface, stereo and bridge modes, phantom power, tone control. 2 Lines level and microphone input. Optional IR remote control.	Unid.	182,58	224,57
	AMC-IRCOM Optional IR remote control for iCOMC2X20 amplifier.	Unid.	29,81	36,67

IMAGEM	REF.MODELO / CARACTERISTICAS	UNID.	€ PVPR	€ PVPR C/IVA
--------	------------------------------	-------	--------	--------------

Mixing Amplifiers

NEW		AMC-MPA30F Media player amplifier with 2 microphone TRS 6.3 jack inputs, AUX/PHONO input, RCA amp input, RCA preamp output, 30W RMS, 100V/70V/25V/4 Ω outputs; built-in USB and SD MMC card reader with recording function and FM tuner	Unid.	228,80	281,42
		AMC-MA30X Amplificador Mix, 2x MIC TRS 6,3 jack, 1x CD, Stereo RCA AUX e Phono, 30W RMS, 100V/16 /8 /4 Ohms outputs. 	Unid.	127,11	156,35
		AMC-MA60 Amplificador Mix, 4x LINE/MIC, 1x LINE inputs, 60W RMS 100V/70V/4 Ohms, REC Outputs, 24V emergency power supply. 	Unid.	265,78	326,91
		AMC-MA120 Amplificador Mix, 4x LINE/MIC, 1x LINE inputs, 120W RMS 100V/70V/4 Ohms, REC Outputs, 24V emergency power supply. 	Unid.	298,13	366,70
		AMC-MA240 Amplificador Mix, 4x LINE/MIC, 1x LINE inputs, 240W RMS 100V/70V/4 Ohms, REC Outputs, 24V emergency power supply.	Unid.	344,36	423,56

5 zone Mixing Amplifiers (Com módulos substituíveis)

NEW		AMC-MMA120X Five zone modular mixing amplifier with 4 MIC, 2 LINE, TEL, Remote Mic inputs. 5 zone selector. 120W RMS, 100V/70V/25V/4 Ω outputs. FM/AM/CD/USB/SD modules to be ordered extra. Possibility to plug in music source module and 5 zone paging microphone Page station 5.	Unid.	383,64	471,88
		AMC-MMA120 Modulo amplificador mixing 5 Zonas, 4x MIC, 2x LINE, 1x TEL inputs, 1x Remote MIC input, 5 speaker selector, 120W RMS, 100V/70V/25V/8 Ohms outputs, opcional: Modulo FM/AM/CD	Unid.	385,96	474,73
		AMC-MMA240 Modulo amplificador mixing 5 Zonas, 4x MIC, 2x LINE, 1x TEL inputs, 1x Remote MIC input, 5 speaker selector, 240W RMS, 100V/70V/25V/8 Ohms outputs, opcional: Modulo FM/AM/CD	Unid.	508,44	625,39
		AMC-MMA240X Five zone modular mixing amplifier with 3 MIC, 3 LINE/MIC, TEL, Remote Mic inputs. 5 zone selector. 120W RMS, 100V and 4Ω outputs. FM/AM/CD/USB/SD modules to be ordered extra. Possibility to plug in music source module and 5 zone paging microphone Page station 5X.	Unid.	496,89	611,17
		AMC-FM/AM/USB/SD Flash Disc e leitor de cartões SD com ficheiros de audio comprimido e sintonizador FM/AM. Compatível com o AMC cinco zonas.	Unid.	194,13	238,78
		AMC-FM/AM/CD/USB CD e Flash Disc com ficheiros de audio comprimido e sintonizador FM/AM. Compatível com AMC 5 zonas.	Unid.	284,27	349,65

Installation Amplifiers

	AMC-A4x120D Amplificador de Potência com 4 canais independentes (D-Class), RMS 120W, 100V/70V/8 Ohms outputs, 4x balanced inputs with gain contro e filtro HPF. Switching power supply.	Unid.	755,73	929,55
	AMC-ia240X 240W installation amplifier for 100V, 70V and 4 Ω sound system. Phoenix output connectors, Phoenix input in parallel to stereo RCA and link output connectors, ground lift. 24V DC power supply.	Unid.	418,31	514,52
	AMC-ia360X 360W installation amplifier for 100V, 70V and 4 Ω sound system. Phoenix output connectors, Phoenix input in parallel to stereo RCA and link output connectors, ground lift. 24V DC power supply.	Unid.	469,16	577,06
	AMC-ia480X 480W installation amplifier for 100V, 70V and 4 Ω sound system. Phoenix output connectors, Phoenix input in parallel to stereo RCA and link output connectors, ground lift. 24V DC power supply.	Unid.	575,47	707,82
	AMC-ia2x250 Two channel 2x250W power installation amplifier for 100V, 70V and 4 Ω sound systems, Switching power supply, phoenix output connector, input gain control, dual or single input mode, output configuration selector, HP filter.	Unid.	450,67	554,32
	AMC-ia4x125 Four channel 4x125 W power installation amplifier for 100V, 70V and 4 Ω sound systems. Switching power supply, phoenix output connector, input gain control, dual or single input mode, output configuration selector, HP filter.	Unid.	543,11	668,03

IMAGEM	REF.MODELO / CARACTERISTICAS	UNID.	€ PVPR	€ PVPR C/IVA
--------	------------------------------	-------	--------	--------------

Wireless Microphones

	AMC-iLive1Handheld iLive1 Handheld true diversity wireless microphone system with 32 selectable channels. Automatic channel synchronization and automatic frequency selection. The microphone signal receiver, handheld microphone transmitter and jack/jack cable are included in every package.	Conjunto	335,11	412,19
	AMC-iLive1Headset iLive1 Headset true diversity wireless microphone system with 32 selectable channels, automatic channel synchronization and automatic frequency selection. The microphone signal receiver, body pack transmitter with head worn, body color condenser microphone and jack/jack cable are included in every package.	Conjunto	335,11	412,19
	AMC-iLive1Lavalier iLive1 Lavalier true diversity wireless microphone system with 32 selectable channels, automatic channel targeting and synchronization with automatic frequency selection. The microphone signal receiver, body pack transmitter with lavalier microphone and jack/jack cable are included in each set.	Conjunto	335,11	412,19
	AMC-iLive1BP Body pack transmitter with LCD display, 4-pin mini XLR microphone input, ON/OFF switch.	Unid.	113,24	139,29
	AMC-iLive1HANDMIC Handheld wireless microphone transmitter. Dynamic cardioid capsule, LCD display. Channel, frequency and battery level are displayed on LCD screen. Transmitter power selector in order to increase battery life. Metal body. For use with iLive 1 receivers only.	Unid.	127,11	156,35
	AMC-iLive2Handheld iLive2 Handheld antenna diversity wireless microphone system with 32 selectable channels with automatic channel targeting and synchronization. The microphone signal receiver, handheld microphone transmitter and jack/jack cable are included in each set.	Conjunto	244,98	301,32
	AMC-iLive2Headset iLive2 Headset advanced diversity wireless microphone system with 32 selectable channels with automatic channel targeting and synchronization. The microphone signal receiver, body pack transmitter with head-worn, body color condenser microphone and jack/jack cable are included in each set.	Conjunto	244,98	301,32
	AMC-iLive2Lavalier iLive2 Lavalier antenna diversity wireless microphone system with 32 selectable channels with automatic channel targeting and synchronization. The microphone signal receiver, body pack transmitter with lavalier microphone and jack/jack cable are included in each set.	Conjunto	244,98	301,32
	AMC-iLive2BP Body pack transmitter with LCD display, 4-pin mini XLR microphone input, ON/OFF switch.	Unid.	85,51	105,18
	AMC-iLive2HANDMIC Handheld wireless microphone transmitter. Dynamic cardioid capsule, LCD display. Channel, frequency and battery level are displayed on LCD screen. Transmitter power selector in order to increase battery life. Metal body. For use with iLive 2 receivers only.	Unid.	99,38	122,23
	AMC-iLive2x2 Dual channel receiver with 32 selectable channels, automatic channel targeting. LCD display indicates RF, AF level, mute, volume, channel or frequency. Balanced XLR and 6,3mm TS Jack audio outputs.	Unid.	383,64	471,88
	AMC-iLive12HM Lightweight, size adjustable headset microphone with condenser capsule. 4 pin mini XLR connector.	Unid.	24,73	30,42
	AMC-iLive12LM Lavalier microphone with condenser capsule and 4 pin mini XLR	Unid.	17,33	21,32
	AMC-iLiveMB12 Rack mount brackets for iLive 1 or iLive 2 wireless receivers (2pcs)	Conjunto	7,40	9,10
	AMC-iLiveMB12x2 Rack mount brackets for two iLive 1 or iLive 2 wireless receivers (2pcs)	Conjunto	13,17	16,20
	AMC-iLive HM Lightweight, adjustable and comfortable headset microphone	Unid.	24,73	30,42
	AMC-iLive LM Lavalier microphone with cardioid polar pattern	Unid.	17,33	21,32
	AMC-iLive MB Rack mount brackets for iLive wireless receivers (2pcs)	Conjunto	6,24	7,68
	AMC-iLive ARP 1 Suporte de Rack para antenas wireless de microfones.	Conjunto	30,51	37,52
	AMC-iLive mini XLR 4-pin mini XLR connector	Unid.	4,39	5,40
	AMC-RS 1 Espaço de Rack para 2 iLives.	Unid.	16,18	19,90

IMAGEM	REF.MODELO / CARACTERISTICAS	UNID.	€ PVPR	€ PVPR C/IVA
--------	------------------------------	-------	--------	--------------

Wireless Microphones

NEW		AMC-UX3 Fixed frequency wireless microphone system with handheld transmitters with dynamic capsule. Available in 4 fixed frequencies 626.63 MHz, 630.40 MHz, 863.425 MHz and 864.900MHz.	Conjunto	150,92	185,63
-----	---	--	----------	---------------	---------------

Microphones

NEW		AMC-PAGESTATION5X Five zone paging microphone for MMA120X and MMA 240X mixing amplifiers.	✓ Em Stock	Unid.	136,36	167,72
		AMC-iSing D Microfone dinâmico de mão (4,5m cabo), -73 dBu, frequência 80 Hz-12,000 Hz, Peso: 360gr.	✓ Em Stock	Unid.	28,89	35,53
		AMC-PAGESTATION Microfone Gooseneck condensador com base de mesa, -36 dB, frequência 50 Hz-18,000 Hz, high quality super cardioid capsule	✓ Em Stock	Unid.	106,31	130,76
		AMC-TALKC1 Microfone Gooseneck condensador, -60 dB, frequência 80 Hz-18,000 Hz	✓ Em Stock	Unid.	54,31	66,80
		AMC-TALKD Microfone Gooseneck dinamico, -76 dB, frequência 150 Hz-12,000 Hz	✓ Em Stock	Unid.	24,27	29,85
		AMC-TALKST Base de Mesa em metal com on/off, switch para microfones com conexão XLR	✓ Em Stock	Unid.	45,76	56,28

Volume Controls

	AMC-VC5RX Volume control with 24V emergency relay and internal switch for active or passive mode selection. 100V/ 5W, 10 steps + OFF	Unid.	10,86	13,36	
	AMC-VC30RX Volume control with 24V emergency relay and internal switch for active or passive mode selection. 100V/ 30W, 10 steps + OFF	Unid.	14,56	17,91	
	AMC-VC60RX Volume control with 24V emergency relay and internal switch for active or passive mode selection. 100V/ 60W, 10 steps + OFF	 Em Stock	Unid.	17,33	21,32
	AMC-iBOX Caixa para instalação para VC5RX, VC30RX e VC60RX	 Em Stock	Unid.	2,54	3,13

Speaker Cables

	AMC-OFCFR2x0.82mm 18 AWG flame retardant e oxygen free professional cabo coluna 2x0.82mm. Cor: Laranja ou Cinza (m2)	✓ Em Stock	Metro (Bobines 200m)	1,18	1,45
	AMC-OFCFR2x1.5mm 16 AWG flame retardant e oxygen free professional cabo coluna 2x1.5mm. Cor: Laranja ou Cinza (m2)	✓ Em Stock	Metro (Bobines 200m)	1,43	1,76

Accessories

	AMC-TCB1 Caixa de ligações de mesa. AC power sockets x 2, pass through cable slots x 9. Dimensões 136mm x 170mm x 150 mm	✓ Em Stock	Unid.	187,20	230,26
	AMC-TR10 Transformador (10W), 4 steps		Unid.	8,78	10,80
	AMC-TR20 Transformador (20W), 4 steps		Unid.	9,48	11,65

IMAGEM	REF.MODELO / CARACTERISTICAS	UNID.	€ PVPR	€ PVPR C/IVA
--------	------------------------------	-------	--------	--------------

Accessories

	AMC-TR30 Transformador (30W)	Unid.	13,64	16,77
	AMC-TR50 Transformador (50W)	Unid.	15,02	18,48
	AMC-MB6 para VIVA3 302 Mounting bracket for 6 pcs. of VIVA3 302 cluster	Conjunto	50,84	62,54
	AMC-MB6 para VIVA3 502 Mounting bracket for 6 pcs. of VIVA3 502 cluster	Conjunto	55,47	68,22
	AMC-3POLECT 3 terminais em cerâmica, Dimensões 34x18x16mm	Unid.	2,54	3,13
	AMC-MK 1.5 XLR 3-pin XLR Male to 3-pin XLR Femêa Balanced Cable - 1.5 m	Unid. 	25,88	31,84
	AMC-MK 3 XLR 3-pin XLR Male to 3-pin XLR Femêa Balanced Cable - 3 m	Unid. 	27,73	34,11
	AMC-MK 5 XLR 3-pin XLR Male to 3-pin XLR Femêa Balanced Cable - 5 m	Unid. 	30,04	36,95
	AMC-MK 1.5 XLR/KL 3-pin XLR Macho a 6.3mm jack stereo - 1.5 m	Unid.	26,81	32,97
	AMC-MK 3 XLR/KL 3-pin XLR Macho a 6.3mm jack stereo - 3 m	Unid.	28,43	34,96
	AMC-MK 5 XLR/KL 3-pin XLR Macho a 6.3mm jack stereo - 5 m	Unid.	31,66	38,94
	AMC-NC3MXX Conector Neutrik	Unid.	6,70	8,24
	AMC-NC3FXX Conector Neutrik	Unid.	8,09	9,95

Marketing Merchandise

	HY 1180 Headphones Portateis, 32 Ohm, 20-20'000Hz	Unid.	3,70	4,55
	HY 1880 Headphones Portateis, 600 Ohm, 20-20'000Hz	Unid.	6,70	8,24

ULTIMA ATUALIZAÇÃO | JULHO 2016

CONDIÇÕES GERAIS DE FORNECIMENTO

Esta tabela substitui e revoga as anteriores.
Os preços poderão ser sujeitos a alterações sem aviso prévio.
Preços sujeitos a iva e taxas legais em vigor.



SEDE PORTO

Rua Companhia dos Caolinos Nº38
4460-205 Senhora da Hora
MATOSINHOS - PORTUGAL
Tel. +351 229 558 456
Fax. +351 229 558 457

DELEGAÇÃO LISBOA

Centro de Escritórios Panoramic
Av. do Atlântico - Lote 1.19.02 - 3.12
1990-019 Parque das Nações
Lisboa - Portugal
Tel. +351 212 405 070
Fax. +351 210 920 609