POWER AMPLIFIERS

A Power Amplifiers



Professional two channel power amplifiers.



Modern design with ultra slim body. Screw terminal speaker connectors and balanced Phoenix input connectors with a fan cooling system and bridge mode selector. Can be used for live music, background music and voice. These professional power amplifiers are designed in order to meet the increasing demand of low power amplifiers for the installation market.

These stereo power amplifiers have complete circuit fault protection and offer a superior performance.





| Technical Specifications | A 100 |
|--------------------------|---|
| Output power | Rated 100 W + 100 W (4 Ω), 70 W+70 W (8 Ω) |
| Power supply | ~230 V/115 V 50/60Hz |
| Outputs | Screw terminal block |
| Inputs | Connectors - Balanced Phoenix, Impedance - 10 k Ω , input sensitivity - 0,775V |
| Frequency response | 25 Hz - 25 kHz |
| THD | < 0,03 % |
| Signal / noise ratio | > 100 dB |
| Damping factor | $>$ 400 at 8 Ω |
| Controls | Power switch, volume, mode selector |
| Indicators | Power, signal, clip, protect |
| Dimensions | 482 mm x 45 mm x 320 mm |
| Weight | 7,8 kg |
| Mounting | 19" rack |
| Colour | Black (RAL 9017) |