

User Switch Settings and Functions in Local Mode

CONTROL

	User Switch Mode	SWITCH FUNCTION LED Color	DEFAULT MODE LED Color
Default	Toggle (mute on power up)	Green	Red
1st Press	Toggle (talk on power up)	Green	Green
2nd Press	Press to Talk	Red	Red
3rd Press	Press to Mute	Red	Green

To reduce the environmental impact of a multi-language printed document, product information is available online at www.audio-technica.com in a selection of languages.

Afin de réduire l'impact sur l'environnement de l'impression de plusieurs langues, les informations concernant les produits sont disponibles sur le site www.audio-technica.com dans une large sélection de langue.

Para reducir el impacto al medioambiente, y reducir la producción de documentos en varios leguajes, información de nuestros productos están disponibles en nuestra página del Internet: www.audio-technica.com.

Para reduzir o impacto ecológico de um documento impresso de várias linguas, a Audio-Technica providência as informações dos seus produtos em diversas linguas na www.audio-technica.com.

Per evitare l'impatto ambientale che la stampa di questo documento determinerebbe, le informazioni sui prodotti sono disponibili online in diverse lingue sul sito www.audio-technica.com.

Der Umwelt zuliebe finden Sie die Produktinformationen in deutscher Sprache und weiteren Sprachen auf unserer Homepage: www.audio-technica.com.

Om de gevolgen van een gedrukte meertalige handleiding op het milieu te verkleinen, is productinformatie in verschillende talen "on-line" beschikbaar op: www.audio-technica.com.

本公司基於減少對環境的影響，將不作多語言文件的印刷，有關產品訊息可在 www.audio-technica.com 的官方網頁上選擇所屬語言及瀏覽。

本公司基于减少对环境的影响，将不作多语言文档的印刷，有关产品信息可在 www.audio-technica.com 的官方网页上选择所属语言和浏览。

For customers in the USA

FCC Notice

Warning:

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Caution:

You are cautioned that any changes or modifications not expressly approved in this manual could void your authority to operate this equipment.

Note:

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

For customers in Canada

ISED statement

CAN ICES-003(B) / NMB-003(B)

中国大陆客户联系资料

制造商：铁三角有限公司

代理商：北京铁三角技术开发有限公司华南分公司

地址：广州市番禺区南村镇万博二路180号粤海广场2505房

电话：+86 (0)20-37619291

生产标准：GB4943.1-2022, GB/T9254.1-2021

原产地：日本

印刷版本一：2023年11月

香港及澳門客戶聯絡資料

總代理：鐵三角(大中華)有限公司

地址：香港九龍紅磡民裕街51號凱旋工商中心第二期9樓K室

電話：+852-23569268

台灣客戶聯絡資料

進口廠商／製造廠商：台灣鐵三角股份有限公司

地址：桃園市中壢區過嶺里福達路2段322巷6號

服務專線：0800-774-488 原產地：日本

Specifications




Frequency response	20-20,000 Hz
Low frequency roll-off	80 Hz, 18 dB/octave
Input impedance	1.4 kΩ
Maximum input levels	-10 dBu @ +30 dB gain -20 dBu @ +40 dB gain -30 dBu @ +50 dB gain
Signal-to-noise ratio ¹	68 dB, 1 kHz at 1 Pa
Power requirements	PoE IEEE802.3af standard
Power consumption	1.5W
Microphone phantom power	12V DC
Switches	Local Mode: Touch-sensitive capacitive-type user switch function: toggle (mute on power up), toggle (talk on power up), momentary on, momentary off; Low-cut filter: flat, roll-off; Gain: +30 dB, +40 dB, +50 dB; Phantom power: 12V DC, off Remote Mode: Low-cut and Gain via third-party software*
Weight	785 g (28 oz)
Dimensions	133.0 mm (5.24") maximum length, 93.8 mm (3.69") maximum width, 46.2 mm (1.82") maximum height
Input connector	3-pin XLRF-type
Output connector	Physical level: standard Ethernet
Dante network	Connector: single RJ45 Cable quality: Shielded CAT5 or CAT6 recommended Transmission speed: 100 Mbps

In the interest of standards development, A.T.U.S. offers full details on its test methods to other industry professionals on request.

1 Pascal = 10 dynes/cm² = 10 microbars = 94 dB SPL

¹ Typical, A-weighted, using Audio Precision System One.

Specifications are subject to change without notice.



audio-technica