

elipson | Performance I300

INTEGRATED AMPLIFIER



Discover the I300 integrated amplifier, the jewel of Elipson's PERFORMANCE range. With an effective power of 2x130 W rms at 4 & 8 ohms, the I300 is equipped with cutting-edge ESS Sabre technologies, in Class D with integrated PFC to offer you an exceptional sound experience.

The Line In 1 and 2 - RCA analog inputs and USB, optical and coaxial S/PDIF digital inputs allow you to easily connect your favorite audio sources. Additionally, with LAN, WIFI, and Bluetooth connectivity (Airplay2, Chromecast, UpNp, DLNA) coupled with the ELIPSON Multiroom application, you can easily stream music from your compatible devices.

The 6.35mm Jack headphone output also allows you to enjoy your music without disturbing others. With the I300, you can enjoy a superior audio experience and easy connectivity, all in an elegant case designed for demanding audiophiles.



TECHNICAL

Type

Integrated amplifier

Remote control

IR- multi functions

Technology

ESS Sabre + Class D with integrated PFC

Main Power

100 - 240 V 50 / 60 Hz

Nominal power Wrms into 4 & 8 Ω

2 x 130 W RMS

Power consumption

< 0,5 W standby (EuP 2013) / 0,24 W

Frequency response

20 Hz - 50 kHz

Signal noise ratio

112 dBA

Analogue Inputs

Line In 1 and 2 - RCA

Numerical inputs

USB – Optical and Coaxial S/PDIF

Streamer

LAN – WIFI – Bluetooth (Airplay2, Chromecast, UpNp, DLNA) ELIPSON App

Outputs

Sub
(Cut-off frequency 400 Hz - slope 18 dB/oct)

Supported sample rate

Hi-Res : 24 Bit - 192 kHz

Headphone output

Jack 6.35 mm

Standby mode

Auto : Wake up / Off

FINISHES

Gun grey anodizing / Satin black top cover

NICE TO KNOW



Designed, engineered and made
in France

DIMENSIONS WEIGHT

Dimensions

W430 x D287 x H80 mm
(with feet and connectors)

Net weight

TBC

PACKAGING

Dimensions packaging

TBC

Gross weight

TBC