

SPECIFICATIONS

Type	In-ceiling speaker - 100V
Available powers in 100V mode	15W / 8W / 4W / 2W
Loudspeaker	2-way coaxial Mid-bass : 165 mm paper cone, rubber edge Tweeter : 19 mm silk dome, orientation 35° in all directions
Frequency response (± 3dB)	70 Hz - 20 kHz
Sensitivity	87 dB/1W/1m
Low impedance mode	8 Ohms (100W max)
Crossover frequency	3200 Hz - LP 12dB / HP 18 dB
Colour	White (ready to paint)

Dimensions	Ø230 x D102 mm
Cut-out dimensions	Ø200 mm
Weight	2,1 kg
Packaging (unit)	Brown cardboard
Dimensions	W296 x H130 x D279 mm
Weight	2,27 kg
Overbox (8 pcs)	Brown cardboard
Dimensions	W624 x H272 x D584 mm
Net / Gross weight	11,6 kg / 18 kg

In-ceiling and in-wall speakers range

IN-CEILING SPEAKERS



IC 4
In-ceiling speaker



IC 6
In-ceiling speaker




IC 6ST
In-ceiling speaker




IC 8
In-ceiling speaker



IC 8 ultra slim
In-ceiling speaker



INF 6
Infinite in-ceiling
high end speaker



INF 8
Infinite in-ceiling
high end speaker

IN-WALL SPEAKERS



IW 6
In-wall speaker



IW 8
In-wall speaker



IW 14C
In-wall speaker

ACCESSOIRES



SQ4
Square grill
for IC4 speaker



SQ6
Square grill
for IC6 and IC6ST speakers



SQ8
Square grill
for IC8 speaker



IW6 Back box
Back box
for IW6 speaker



IW8 Back box
Back box
for IW8 speaker