

## SPECIFICATIONS

Type	In-ceiling speaker - 100V
Available powers in 100V mode	30W / 20W / 10W / 5W
Loudspeaker	2-way coaxial Mid-bass : 210 mm paper cone, rubber edge Tweeter : 25 mm silk dome, orientation 35° in all directions
Frequency response (± 3dB)	55 Hz - 20 kHz
Sensitivity	87 dB/1W/1m
Low impedance mode	8 Ohms (125W max)
Crossover frequency	2800 Hz - LP 12 dB / HP 18 dB
Colour	White (ready to paint)

Dimensions	Ø290 x D122 mm
Cut-out dimensions	Ø242 mm
Weight	2,6 kg
Packaging (unit)	Brown cardboard
Dimensions	W330 x H153x D313 mm
Weight	3,35 kg
Overbox (8 pcs)	Brown cardboard
Dimensions	TBC
Net / Gross weight	TBC

## In-ceiling and in-wall speakers range

### IN-CEILING SPEAKERS



**IC 4**  
In-ceiling speaker



**IC 6**  
In-ceiling speaker




**IC 6ST**  
In-ceiling speaker




**IC 8**  
In-ceiling speaker



**IC 8 ultra slim**  
In-ceiling speaker



**INF 6**  
Infinite in-ceiling  
high end speaker



**INF 8**  
Infinite in-ceiling  
high end speaker

### IN-WALL SPEAKERS



**IW 6**  
In-wall speaker



**IW 8**  
In-wall speaker



**IW 14C**  
In-wall speaker

### ACCESSOIRES



**SQ4**  
Square grill  
for IC4 speaker



**SQ6**  
Square grill  
for IC6 and IC6ST speakers



**SQ8**  
Square grill  
for IC8 speaker



**IW6 Back box**  
Back box  
for IW6 speaker



**IW8 Back box**  
Back box  
for IW8 speaker