



## Laia Cute 12x/30x

Laia Cute 12X / 30X is the perfect camera for any meeting room or auditorium regardless of the technology used. You will also have a great image quality thanks to the "crystal clear" sensor and its optical zoom of up to 30X.

The impressive FullHD image offered by its 1 / 2.7" Panasonic CMOS sensor up to 60 ips coupled with its autofocus technology, making our Laia Cute possibly the highest quality camera in its segment.



12X to 30X optical zoom (depends on the chosen model)



USB 3.0 (2.0), HDMI and RJ45 PoE



Up to 1080p 60fps on USB3.0



Up to 255 presets via web, joystick, remote control or software



Automatic camera gyroscope for your corporate environments

Compatible with:



# POSSIBLY THE BEST CAMERA USB, HDMI & ETHERNET OF THE WORLD

## PROFESSIONAL WARRANTY

3 year "Prime support" warranty 24 hrs advanced replacement

### FEATURES

<b>Image sensor</b>	1 / 2.7" high quality Panasonic CMOS sensor
<b>Effective Pixels</b>	5.0 MP sensor. 2.07MP, effective 16: 9
<b>Video format</b>	1920X1080P60 / 50/30/25; 1280X720P60 / 50/30/25; 960X540P30; 640X360P30; 640X480P30; 352X288P30; 960X540P30;
<b>Optical zoom</b>	12X to 30X Extra digital zoom: 10X
<b>Vision angle</b>	72.5° ~ 65° (depending on lens)
<b>Iris</b>	F1.6 - F4.7 (depending on model)
<b>Low illumination</b>	Minimum 0.01 Lux. Recommended minimum 0.5Lux (F1.8, AGC ON)
<b>DNR</b>	2D & 3D Digital noise reduction
<b>White balance</b>	Auto / Manual / One push / 3000K / 3500K / 4000K / 4500K / 5000K / 5500K / 6000K / 6500K / 7000K
<b>Focus</b>	Auto / Manual / One push
<b>Electronic trigger</b>	Auto / Manual
<b>BLC</b>	On / off
<b>WDR</b>	OFF / Dynamic level adjustment
<b>Video settings</b>	Brightness, Color, Saturation, Contrast, Sharpness, Black and white mode, Gamma curve
<b>SNR</b>	≥55dB

### INTERFACE AND PROTOCOL

<b>Video output</b>	HDMI, LAN, USB3.0, USB2.0, CVBS
<b>Streaming video</b>	Dual Stream Out
<b>Multiple image code source output</b>	HDMI, LAN, USB3.0
<b>Video compression</b>	LAN Interface: H.265, H.264, Dual stream output USB3.0 interface: Main stream supports YUY2, MJPEG, H.264, NV12, H.265 Secondary stream support YUY2, MJPEG, H.264, NV12
<b>LAN</b>	LAN (10/100/1000 BASE-TX), PoE
<b>Network protocol</b>	RTSP, RTMP, ONVIF, GB / T28181; Compatible with VISCA control protocol. Supports remote update and restart
<b>Control port</b>	RS232, RS485
<b>Control protocol</b>	Protocol: VISCA / Pelco-D / Pelco-P; Baud Rate: 115200/9600/4800 / 2400bps
<b>Power supply</b>	HEC3800 Outlet (DC12V) with PoE
<b>Power adapter</b>	AC110V-AC220V input, DC12V / 1.5A output
<b>Power input</b>	DC12V ± 10% , 1A (Max)
<b>Consumption</b>	12W (max)

### USB FEATURES

<b>Pan / tile rotation</b>	-170° ~ +170° , -30° ~ +90°
<b>Preset speed</b>	Pan: 120° sec, Tilt: 70° sec
<b>Number of presets</b>	255 presets (10 via remote control)
<b>Gyroscope</b>	Automatic gyroscope

### OTHER PARAMETERS

<b>Temperature during operation</b>	-10 °C ~ +50 °C, 20% ~ 80%
<b>Storage temperature</b>	-10 °C ~ +60 °C, 20% ~ 95%
<b>Dimensions</b>	180mm x 115mm x 149mm
<b>Package weight</b>	1.15 Kg
<b>Use</b>	Inside
<b>Package</b>	12V / 1.5A power supply, remote control, manual, Warranty card.
<b>Optional gadgets</b>	Wall bracket included
<b>Warranty</b>	3-year advanced replacement warranty, extendable up to 5 years.

Headquarters:

Po. Europa, 26 Pta. 1 Of.3  
S.S. de los Reyes 28703  
Madrid- Spain

After-sale service:

C/Brújula, 4 Pol. Ind. PISA  
41927 Mairena del Aljarafe  
Sevilla - Spain



CUTE FAMILY - USB HDMI CAMERA