



Laia Cute VoiceTrack is our exclusive camera with autofocus and speaker tracking, with 12x optical zoom. Unique technologies that in practice perform a mix of intelligent voice and face tracking, so that if two speakers speak at the same time, the shot will open up to capture both of them in the image.

Main characteristics



12X optical zoom for a close-up in Full HD



Automatic framing of the speaker during his or her presentation



USB camera with HDMI



Compatible with Barco's ClickShare Conference






























VoiceTrack Specifications: P/N: CVT

Tracking camera

Image sensor: 1/2.8" CMOS, 2MP

Focal: f = 3.9 mm - 46.8 mm

Iris: F1.6-F2.8 Zoom: Optical: 12x

FOV: Horizontal 72.5° - 6.3°.

Focus: Auto, Manual, PTZ Push, One Push

Shutter speed: $1/25 \sim 1/10,00$

AGC: Auto, Manual

White Balance: Auto, Indoor, Outdoor, One Push, Manual, Auto Track.

Exposure: Auto, Manual, Shutter Priority, Iris Priority.

SN Ratio: ≥50dB

BLC: Yes

Full vision camera

Image Sensor: 1/2.5" 4K CMOS Sensor, 8.57MP

Lens: 2.8mm focus, 4X digital zoom

FOV: 98° DNR: 2D and 3D

Video adjustment: Supports ePTZ

Pan: $-90^{\circ} \sim +90^{\circ}$, $0.1^{\circ} \sim 100^{\circ}$ / s **Tilt:** $-30^{\circ} \sim +90^{\circ}$, $0.1^{\circ} \sim 80^{\circ}$ /s

No. of presets: 64

RED

Maximum image size: 1920×1080@60fps Video compression: H.264/H.265/MJPEG

Audio compression: AAC

Protocol: HTTP, RTSP, RTMP, RTP, TCP, UDP, ONVIF.

Multi-Stream: Supports 1x close view, 1x full view, 1x switching.

Interface

SDI: 1×3G-SDI, Video format: 1080P60/50/30/25, 720P60/50

HDMI: 1xHDMI, Video format: Same as SDI

USB: 1×USB2.0, supports UVC/UAC.

Audio input: 2×3.5mm INLINE, including a reference audio input with echo cancellation.

Network interface: 1x10M/100M RJ45

General

Control protocol: VISCA

Address: 1 - 6

Power supply: DC12V

Consumo de energía: <20W

Working temperature: 0°C ~ +40°C Storage temperature: -20°C ~ +60°C Dimension: 245mm x 145mm x 165mm

Peso: <2Kg

