







myTeam TP100S

P/N: TP-100S

Supports standard SIP and H.323 protocols. Compatible with industry standard endpoints, High definition video, 1080P, with low bandwidth, Multiple microphone signal inputs, High network security, Multiple 1080P HD video inputs and outputs, Audio processor (DSP), API, Infrared transmission, Local and remote recording and transmission, QoS QoS function, Remote configuration and management.

Main characteristics

| | | | |
|--|--|---|--|
|  <p>PiP / PoP</p> |  <p>Remote control IR</p> |  <p>200mm x 428mm x 44.5mm</p> |  <p>3.2Kg</p> |
|--|--|---|--|



TP100S Specifications: P/N: TP-100S

Protocols and standards

Communication: ITU-T H.323, IETF SIP.

Video: H.261, H.263, H.263+, H.263++, H.264, H.264 SVC, H.264 High Profile

Audio: G.711, G.722, G.722.1*, G.722.1C*, AAC-LD, G.726, SILK

Dual Transmission: ITU-T H.239, BFCP.

Network: TCP/IP, DHCP, SSH, HTTP, HTTPS with SSL/TLS, RTP, RTCP, RFC3261, RFC3264, RFC2190, RFC3407, RFC2833, RFC4585(RTP/AVPF), SNMP, ARP, RTMP

Others: H.221, H.224, H.225, H.235, H.241, H.245, H.281, H.350, H.460, T.140, DTMF, FEC anti-lost packets.

Video specifications

Video resolution: 1080P@ 1024Kbps (minimum) // 720P @ 512Kbps (minimum) // w448P/4SIF/4CIF @ 256Kbps (minimum) // w288P/SIF/CIF @ 128Kbps (minimum)

Graphic resolution: Input: VGA (640x480), SVGA (800x600), XGA(1024x768), WXGA(1280x768), WXGA (1280x800), 1280x960, SXGA(1280x1024), 1360x768, 1366x768, 1440x900, 1600x900, 720p(1280x720), 1080p(1920x1080)

- Codec: 800x600, 1024x768, 1280x1024, 1280x720, 1920x1080

- Output: 800x600, 1024x768, 1280x1024, 1280x720, 1920x1080

Dual Streaming: Dual Stream1080p or Dual Stream 720p

Other: Supports PiP, PoP and other display modes.

Network and security

Network: Video Forward Error Correction (FEC), Automatic Repeat-reQuest (ARQ) etc.

Security: H.235, encryption (AES-128, AES-256) // TLS & SRTP // Administrator password SSH/HTTPS

Firewall Traversal: H.460, ICE

Bandwidth

IP: 64kbps ~ 8Mbps

Integration with cloud platforms

Support Brands: Go Facing

Connectivity

Audio In: 2x RCA , 2x XLR Microphone Input, 1x HDMI Audio Input, 2x USB 2.0, 1x RJ45 Digital Microphone Input

Audio Out: 2x RCA, 2x HDMI Audio Output

Video In: 1x HDMI, 1x DVI-I (HDMI, VGA/YPbPr) 1x 3G-SDI

Video Out: 3x HDMI, 1x 3G-SDI

USB flash disk: 2x USB2.0

Network: 1x RJ45: 10/100 Base-T

Control: 1x RJ45: RS232 for VISCA

General

Dimensions and weight: 200mm x 428mm x 44.5mm // 3.2Kg

Electrical: Supply voltage: AC 100V ~ 240V // Max. power consumption: 50W

Environmental conditions: Temperature: 0°C ~ 40°C (operation) // Humidity: 10% ~ 80% (operation)

Supplied accessories: Remote control IR x1 // AC cable x1 // Quick user's guide



Headquarters:
Po. Europa, 26 Pta. 1 Of. 3
S.S. de los Reyes 28703
Madrid - Spain

After-sales service:
C/Brújula, 4 Pol. Ind. PISA
Mairena del Aljarafe 41927
Seville - Spain