



t-Pod Wifi / Dual

P/N: TPW



The Laia t-Pod Wifi connects with Plug & Play to any PC and Mac, via WiFi ad-hoc, ensuring a much higher quality compared to Bluetooth solutions. Compatible with Microsoft, WebRTC, Webex, GoToMeeting, Pexip, Zoom, GoFacing, or Veedeeo among other platforms.

Main characteristics



Use of 2.4 GHz band - WiFi - to ensure high-fidelity sound



USB 3.0 (compatible with 2.0), to create a seamless connection for audio




Plug & Play solution: no software installation required



High sensitivity omnidirectional microphones with echo and noise cancellation



Up to 6 meters distance without loss of sound quality



Specifications Wifi / Dual | P/N: TPW

Technical specifications

Microphone: Cardioid microphones 20-8000Hz

Speaker: 3.94" antimagnetic loudspeaker.

Audio: Dual speaker / Digital audio processing / 256 ms echo cancellation / Dynamic noise reduction / Full duplex / 360° pickup range.

Battery: 7-10 hours (integrated lithium).

Adapter: 2.4G wireless USB

Power supply: 1.5m USB

Dimensions: 155 x 148 x 37 mm

Weight: 340g (single speaker)

Color: Black

Network interface: USB 2.0 (USB 1.1 compatible) : 3.5 mm audio interface (output)

Power supply: USB power supply (DC 5V / 500mA) and integrated lithium battery.

Operating system: Windows 8 / Windows 7 / Windows 10 / Windows XP., etc.

Functions: Support audio software / Skype, Wechat, QQ ect. / Mute microphone / Speaker mute / Volume up and down / Indicator / 2.4G wireless connection / Activate headset.

Certification: CCC

Product performance standard: YD/T 993-1998 __ GB/T 9254-2008 __ GB 4843.1-2011.

2.4G USB adapter: 2.4 G RF and data processing / Foldable SMA antenna

Keyboard: Insert value from technical specification.

LED indicators

Triangular indicator on: in operation

Left indicator on: speaker muted

Right indicator on: MIC mute

Left indicator flashing: volume adjustment

Right indicator in orange: full charge

Recommended conditions

Temperature: 5°~44°

Humidity: 20~85% non-condensing

Nivel de ruido: <48db

Storage temperature: -10°~55°

Tiempo de reverberación: <0,5 segundos

Warranty

Prime Support: 3 years (*extendable to 5 years)



Headquarters:
Po. Europa, 26 Pta. 1 Of. 3
S.S. de los Reyes 28703
Madrid - Spain

After-sales service:
C/Brújula, 4 Pol. Ind. PISA
Mairena del Aljarafe 41927
Seville - Spain