

PH3501QL Laser Projector

Datasheet



The brightest choice for premium visual experiences

Projection is making pioneering new advancements with the NEC PH3501QL 4K RB laser projector delivering 40,000 center lumens brightness. The new flagship model harnesses the best of both laser phosphor and RGB laser technologies resulting in a powerful projector which delivers compelling benefits in terms of cost, operational efficiency and immersive image quality.

With higher brightness, greater detail, more accurate colours beyond rec709 colour space and further installation flexibility you can deliver an unmatched visual experience that will set new standards. The use of a red and blue laser light source goes beyond the colour and brightness output of traditional laser phosphor projection systems providing a brilliant image with high uniformity. The efficient light processing system has a low initial cost compared to RGB laser projectors and delivers huge savings in operational costs compared to Xenon based projection systems by avoiding lamp and filter replacements.

This projector is a premium solution for fixed installations in multi-purpose sports and events halls, theatres, museums and leisure parks as well as for most demanding mapping applications and for rental and staging purposes.

Benefits

Outstanding picture quality – super-bright 40000 center lumen RB laser projection, with real 4K resolution and wide colour space, combined with an homogeneous and contrast-rich laser image quality ensures stunning presentations and impressions.

Enjoy a Lower TCO – highest reliability, maintenance free operation, low power consumption and up to 20000 hours life; the Laser light source results in a significantly lower total cost of ownership.

Maximum installation flexibility – the extra wide vertical +/- 50% and horizontal +/- 17% lens shift combined with a selection of wide zoom bayonet lenses guarantees a hassle-free installation and facilitates easy replacement of old projectors.

Bringing Cinema Quality to the mainstream – NEC's cinema approved digital projection technology, renowned for its smooth, colour rich video processing is integrated within this installation projector.

Future-proof signal connectivity and processing – numerous 4K resolution inputs such as Quad 3G SDI, 2 x DisplayPort, 2 x HDMI plus an optional slot for 4K/UHD OPS Slot-in PCs provide "pixel-free viewing" on a large scale.

Widest application support – portrait mode projection, 360 degree free tilt installation, unique geometric adjustment and 3D support offers unrivalled installation capability.

Relax and rely on laser – stable light output ensures consistent brightness and colour stability over the entire life cycle of the projector.

Cost Saving Device Management – save effort whilst administrating all connected NEC devices from a centralised location by using the NaViSet Administrator 2 software tool.

Product Information

Product Name	PH3501QL
Product Group	Laser Projector
Order Code	60004622

Image

Projection Technology	DC4K Chip - DLP™ Technology
Native Resolution	4096 x 2160 (4K)
Aspect Ratio	17:9
Contrast Ratio ¹	30000:1 (with dynamic contrast)
Brightness ¹	35000 Normal / 28000 Eco ANSI Lumen; 40000 Centre Lumen
Lamp	Laser Light Source
Lamp Life [hrs]	20000
Lens	7 optional bayonet lenses
Lense Adjustment	Motorized
Lens shift	Up to H:±17, V:+50,-50
Keystone correction	+/- 40° manual horizontal / +/- 40° manual vertical
Projection Factor	depending on lens selection
Projection Distance [m]	2 – 50
Screen Size (diagonal) [cm] / [inch]	254 / 100" - 2,540 / 1,000"
Zoom	Motorized
Focus Adjustment	Motorized
Supported Resolutions	4096 x 2160 (4K); 3840 x 2160 (UHD); 2560 x 1600 (WQXGA); 2048 x 1080 (2K); 1920 x 1200 (WUXGA); 1080i/50/60; 1080p/24/25/30/50/60; 720p/50/60; 640 x 480 (VGA); 576i/50; 576p/50; 480i/50; 480p/60

Connectivity

Digital	Input: 1 x HDBaseT; 2 x DisplayPort; 2 x HDMI™ supporting HDCP; 4 x 3G-SDI
Control	Input: 1 x D-Sub 9 pin (RS-232), Ethernet
Option Slot	Input: 1 x Slot for optional OPS modules
LAN	1 x RJ45
USB	1 x Type A (USB 2.0 high speed)
Video Signals	NTSC; NTSC 4.43; PAL; PAL-M; PAL-N; PAL60; SECAM

Remote Control

Input:	1 x 3.5 mm Stereo Mini Jack
Remote Control	Auto Adjust; AV Mute; Direct Info; Direct Source Select; Eco Mode Control; Freeze; Full Lense control; Help-function; ID Select; ID set; Input Control; On Screen On/Off Selection; PBP/POP Function; PIP Function; Power (On-OFF); Select (up, down, left, right); Shutter function; Test Picture; Zoom/Focus and Lens Shift Control

Electrical

Power Supply	200-240 V AC; 50 - 60 Hz
Power Consumption [W]	4705 Normal Mode

Mechanical

Dimensions (W x H x D) [mm]	697 x 455 x 1,180 (without lens and feet)
Weight [kg]	169
Fan Noise [dB (A)]	53 / 55 (Eco / Normal)
Colour Versions	Black

Ergonomics

Safety and Ergonomics	CE; ErP; RoHS; TÜV GS
-----------------------	-----------------------

Additional Features

Special Characteristics	3D ready; 4K/60Hz interfaces; Cinema Quality Picture (CQP) Processing for best image quality; Edge Blending Function; Free Tilt; Geometric Correction; LAN; LAN control; Lens Shift (vertical 0.55 max/0.55 max, horizontal ± 0.22 max.); Light Source Adjustment; Portrait Setting; RS-232 Control; Test Pattern; Timer-Function
-------------------------	---

Green Features

Energy Efficiency	Laser Light Source
Ecological Standards	ErP compliant

Warranty

Projectors	3 years pan-European service
Light Source	3 years or 10000h (whatever comes first)

Optional Accessories

Lenses	L2K-10F1 (0.9:1); L2K-30ZM (2.71-3.89:1); L2K-43ZM1 (3.7-5.3:1); L2K-55ZM1 (4.8-7.4:1); L4K-11ZM (1.24-1.72:1); L4K-15ZM (1.52-2.1:1); L4K-20ZM (1.98-3.4:1)
--------	--

¹ Compliance with ISO21118-2012



This product has been equipped with a laser module and is classified as Class1 of IEC60825-1 Ed3 2014 and is classified as RG2 of IEC62471-5 Ed1 2015.

DO NOT LOOK DIRECTLY INTO THE BEAM.

This document is © 2018 NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 28.02.2018