
# SHARP/NEC

MultiSync® EA242F LCD 23.8" Enterprise Display

# **Datasheet**





#### Powering workspace communications

Powering your PC/notebook and all your devices through a single cable, the MultiSync® EA242F is your workspace hub; no docking station required, the 65W USB-C connection means an efficient, clutter-free workstation from which to manage your communications. Easily increase your display area using DisplayPort-out to daisy-chain multiple displays, no additional cabling required.

User comfort is fundamental with full height adjustment, tilt, pivot and swivel supporting customised personal setup, whilst builtin low blue light technologies guard against eye fatigue without compromising true-to-life colour performance. Available in black or white, the 24" EA242F complements office interior design and ergonomics.

The connectivity advantage continues beyond USB Type-C with DisplayPort, HDMI, VGA and USB A for fully future-proof flexibility supporting new open office standards in hot desking and 'bring your own device.'

#### **Benefits**

In-demand display size - the popular 23.8" display with Full HD resolution is the perfect size for busy office workspaces.

Future-proof flexibility - wide connectivity provides high-level flexibility with DP, HDMI, USB Type C, USB A and audio output.

Clutter-free workspace - Powerful 65W USB Type-C connectivity manages video, audio, power and USB via a single cable

Easy multi-screen set-up - Daisy-chain multiple display configurations through DisplayPort-out, no additional cables needed

**Maximum attention to health and well-being** - the outstanding ergonomic height adjustment from 0 to 150 mm; eye pleasing built-in Low Blue Light and Flicker-Free technology; plus integrated ambient light sensor all combines to tailor the perfect individual setup to boost productivity.

## **Product Information**

Product Name	MultiSync® EA242F
Product Group	LCD 23.8" Enterprise Display
Order Code	60005246 (WH), 60005032 (BK)

## **Display**

Panel Technology	IPS TFT with W-LED backlight
Screen Size [inch/cm]	24 / 60.47
Screen Aspect Ratio	16:9
Colour Gamuts	101.6 % sRGB; 75.3% AdobeRGB, 72% NTSC
Pixel Pitch [mm]	0.275
Brightness (typ.) [cd/m²]	250
Contrast Ratio (typ.)	1000:1 (5000:1 dynamic contrast ratio)
Viewing Angle [°]	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Response Time (typ.) [ms]	5 (grey-to-grey)
Colours [Mio.]	16.78 (6-bit per colour)

# **Synchronisation Rate**

Horizontal Frequency [kHz]	31.5 - 83
Vertical Frequency [Hz]	50 - 75

## Resolution

Optimum Resolution	1920 x 1080 at 60	1920 x 1080 at 60 Hz			
Supported	1920 x 1080;	1280 x 1024;	1024 x 768;	720 x 480;	
	1680 x 1050;	1280 x 960;	800 x 600;	720 x 400;	
	1440 x 900;	1280 x 720;	720 x 576;	640 x 480	

# Connectivity

Digital	1 x DisplayPort; 1 x DisplayPort out; 1 x HDMI; 1 x USB Type C; USB ver. 3.1 (3 down / 1 up)
Analog	1 x D-sub 15 pin

## **Electrical**

Power Consumption on Mode [W]	15 (Eco Mode 2); 21 (typ.)
Power Savings Mode [W]	0.3
Power Supply	0.9 A/0.5 A; 100-240 V; internal power supply

# **Environmental Conditions**

Operating Temperature [°C]	+5 to +35
Operating Humidity [%]	20 to 80
Storage Humidity [%]	10 to 85
Storage Temperature [°C]	-10 to 60

# **Ergonomics**

Height adjustable stand [mm]	150 (Landscape mode)
Screen Tilt [°]	-5 to 35
Screen Swivel [°]	-170 to 170
Screen Rotate [°]	0 to 90 (landscape to portrait mode)

#### **Mechanical**

Bezel Width [mm]	0.8 (left/right/top); 15.8 (bottom)
Dimensions (W x H x D) [mm]	319.1 x 555.6 - 615.4 x 250 (Portrait mode); 537.7 x 336.6 - 486.6 x 250 (Landscape mode)
Weight [kg]	With stand: 7
VESA Mounting [mm]	100 x 100 (4 points)

#### **Additional Features**

Colour Versions	Black Front Bezel, Black Back Cabinet
Cable Management	yes
Kensington security slot	yes
Plug and Play	DDC2B/2Bi; VESA DDC/CI; VESA DDC2Bi
Audio	Integrated Speakers (1 W + 1 W)
Adjust Functions	Advanced NTAA (Advanced Non-Touch-Auto-Adjustment)
Shipping Content	Control Sync Cable; DisplayPort cable; Monitor; Power Cable; Set-up Manual; USB Cable; USB-C Cable
Safety and Ergonomics	CE; EAC; EnergyStar 8.0; ErP; Flicker-free; ISO 9241-307 (pixel failure class I); PSB; RoHS; TCO 8.0; TÜV Ergonomics; TÜV GS; UL/C-UL or CSA; WEEE
Warranty	3 years warranty incl. backlight; optional 1st to 3rd year 24/7 usage warranty; optional 4th to 5th year warranty extension

## **Green Features**

Energy Efficiency	Ambient light sensor; Energy efficiency class: A+; Human sensor
Ecological Standards	ErP compliant; RoHS compliant; WEEE

			LCD-		
			LCD-	TUEVErgonomics	
LCD-CE	LCD-ERP	LCD-RoHS	TCOValue	ΤÜV	LCD-TUEVGS
CE	ErP	RoHS	TCO 8.0	Ergonomics	TÜV GS

This document is © 2021 Sharp NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 04.02.2021