

DH351

High resolution presentations



- **Lights on viewing – 3600 ANSI lumens**
- **Easy connectivity – HDMI, USB power**
- **Portable and lightweight**
- **Built-in audio**



Project bright Full HD 1080p images with the DH351. Perfect for classroom and meeting room presentations, this projector is designed to be used at any time of day.

Additionally, it boasts ease of use with its single HDMI connection and built-in speaker. You can even use the USB power to connect and power HDMI dongles such as the Google Chromecast.

Specifications

EAN: 5055387663701, Colour: Black

| | |
|--------------------------------|--|
| Display/image | |
| Display technology | DLP™ |
| Resolution | 1080p Full HD (1920x1080) |
| Brightness | 3,600 lumens |
| Contrast ratio | 22,000:1 |
| Native aspect ratio | 16:9 |
| Aspect ratio - compatible | 4:3 |
| Keystone correction - vertical | +/-40° |
| Uniformity | 80% |
| Screen size | 0.71m ~ 7.65m (28" ~ 301") diagonal |
| Lamp info | |
| Light source type | Lamp |
| Lamp watts | 240 |
| Lamp life hours (up to) | 4000 (Bright), 15000 (Dynamic), 10000 (Eco) |
| Optical | |
| Throw ratio | 1.47:1 ~ 1.62:1 |
| Projection distance (m) | 1m - 9.8m |
| Zoom | 1.1 |
| Zoom type | Manual |
| Focal length (mm) | 15.59mm~17.14mm/0.614"~0.675" |
| Native offset | 116% |
| Connectivity | |
| Connections | Inputs 1 x HDMI 1.4a 3D support Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A |
| General | |
| Noise level (typical) | 26dB |
| Noise level (max) | 28dB |
| PC compatibility | FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac |
| 2D compatibility | NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) |
| 3D compatibility | Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 |
| 3D | Full 3D |
| Security | Security bar, Kensington Lock, Password protected interface |
| OSD / display languages | 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese |
| Operating conditions | 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% |
| Remote control | Backlit home remote |
| Speaker count | 1 |
| Watts per speaker | 5W |
| In the box | AC power cord Remote control 2x AAA batteries Basic user manual |
| Optional wireless models | HDcast Pro, WHD200 |
| Power | |
| Power supply | 100 ~ 240V, 50 ~ 60Hz |
| Power consumption (standby) | 0.5W |
| Power consumption (min) | 205W |
| Power consumption (max) | 295W |
| Weight and dimensions | |
| Dimensions (W x D x H) mm | 316 x 244 x 108 |
| Gross weight | 3.81 kg |
| Net weight | 2.8 kg |

