



The **OPEN ROLL** model has been studied to be installed in pretty large rooms like concert halls, cinemas, auditoriums and conference rooms.

Open Roll assures great success in projections thanks to its high quality standard.

This screen has the particular feature to be without housing.

Available in 4:3, 16:9 and 16:10 ratios or bespoke sizes.

MOUNTING BRACKET: SHAFT SIDE

MOUNTING BRACKET: MOTOR SIDE








Kit RF Remote control with external receiver






OPTIONAL pag 62-63


MOUNTING BRACKET: SHAFT SIDE (LEFT)




MOUNTING BRACKET: MOTOR SIDE (RIGHT)



WALL MOUNTING



CEILING MOUNTING



AVERAGE TIME ROLLING UP/DOWN


Sec.

46

48 56

H (cm)

375 450



TECHNICAL SPECIFICATIONS

- Silent motor system provides a smooth and quiet operation

Power: 40 Nm
 Speed: 17 rpm
 Power supply: 230V / 50 Hz
 Consuption: 322 W

· Consuption: 322 MQ

- Strong steel and aluminium construction
- Black dowel bar: height 35 mm. depth 20 mm.
- Standard black bottom border of 10 cm.
- Two mounting brackets for ceiling or for wall
- On/Off switcher included
- Power cable located at **right** side of the screen, seen from the front
- Flame retardant projection surfaces classification M1, M2 and B1
- Side black borders of 5 cm. (optional)

DIMENSIONS measures in cm					
4:3 Ratio Viewing area (WxH)	16:9 Ratio Viewing area (WxH)	16:10 Ratio Viewing area (WxH)	Overall dimensions A - C	Approx. net weight (Kg)	
500 x 375	500 x 281	500 x 313	530 - 505	52	
600 x 450	600 x 337	600 x 375	630 - 605	63	
700 x 525	700 x 394	700 x 437	730 - 705	73	

PROJECTION CLOTHS					
Front projection surfaces	Gain	Rear projection surfaces **no black borders**	Gain		
White	1.2	Rear Plus	1.1		
Matte White	1.2	Front Rear	0.9		
Microholes	1.0				
Ultra HD	1.2				



Warranty: 5 years on the motor - 24 months on the other components