

## Sharp MultiSync® EA272F LCD 27" Enterprise Display

# Datasheet



### Re-imagine your desktop computing experience

With the MultiSync EA Series, Sharp has developed monitor solutions that push the boundaries of what you've come to know as business-class screen performance. The EA Series deliver a completely redesigned chassis with a host of enhanced features, advanced technologies, future-proof connectivity and environmentally friendly benefits. All models utilise IPS LCD panels, which boast the best possible colour accuracy and minimal viewing angle shift.

Every model features LED backlights, enabling a thin and light design. Other green features include ECO Mode™, a carbon footprint meter and an ambient light sensor, which automatically adjusts the brightness to the optimal setting depending on ambient lighting, screen content or both.

## Benefits

**In-demand display size** – the popular 27.0" display with Full HD resolution is the perfect size for busy office workspaces.

**Clutter-free workspace** – Powerful 65W USB Type-C connectivity manages video, audio, power and USB via a single cable

**Future-proof flexibility** – wide connectivity provides high-level flexibility with DP, HDMI, USB Type C, USB A and audio output.

**Easy multi-screen set-up** – Daisy-chain multiple display configurations through DisplayPort-out, no

additional cables needed

**Maximum attention to health and well-being** – the outstanding ergonomic height adjustment from 0 to 150 mm; eye pleasing built-in Low Blue Light and Flicker-Free technology; plus integrated ambient light sensor all combines to tailor the perfect individual setup to boost productivity.

**Product Information**

Product Name	Sharp MultiSync® EA272F
Product Group	LCD 27" Enterprise Display
Order Code	60006216 (BK), 60006218 (WH)

**Display**

Panel Technology	AH-IPS LCD with LED Backlight
Screen Size [inch/cm]	27 / 69
Screen Aspect Ratio	16:9
Colour Gamuts	102 % sRGB; 75.5% AdobeRGB, 72% NTSC
Pixel Pitch [mm]	0.311
Brightness (typ.) [cd/m²]	250
Contrast Ratio (typ.)	1000:1 (5000:1 dynamic contrast ratio)
Response Time (typ.) [ms]	6
Colours [Mio.]	16.777

**Synchronisation Rate**

Horizontal Frequency [kHz]	31.5 - 83
Vertical Frequency [Hz]	55 - 75

**Resolution**

Optimum Resolution	1920 x 1080 at 60 Hz			
Supported	1024 x 768; 1280 x 1024; 1280 x 720;	1280 x 960; 1440 x 900; 1680 x 1050;	1920 x 1080; 640 x 480;	720 x 400 (70 Hz); 800 x 600

**Connectivity**

Digital	1 x DisplayPort; 1 x DisplayPort out; 1 x HDMI; 1 x USB Type C; USB ver. 3.1 (3 down / 1 up)
Analog	1 x VGA

**Electrical**

Power Consumption on Mode [W]	15 (Eco Mode 2); 21 (typ.)
Power Savings Mode [W]	3

Power Supply	0.85 A/0.45 A; 100-240 V; integrated power supply
--------------	---

---

## Environmental Conditions

---

Operating Temperature [°C]	+5 to +35
----------------------------	-----------

Operating Humidity [%]	20 to 80
------------------------	----------

Storage Humidity [%]	10 to 85
----------------------	----------

Storage Temperature [°C]	-10 to 60
--------------------------	-----------

---

## Ergonomics

---

Height adjustable stand [mm]	150 (Landscape mode)
------------------------------	----------------------

Screen Tilt [°]	-5 to 35
-----------------	----------

Screen Swivel [°]	-170 to 170
-------------------	-------------

Screen Rotate [°]	-90 to 90 (landscape to portrait mode)
-------------------	--

---

## Mechanical

---

Bezel Width [mm]	0.8 (left and right); 0.8 (top); 15.8 (bottom)
------------------	--

Dimensions (W x H x D) [mm]	359.8 x 628.4 - 651.6 x 250 (Portrait mode); 610.2 x 377.3 - 527.3 x 250 (Landscape mode)
-----------------------------	---

Weight [kg]	With stand: 9.2
-------------	-----------------

VESA Mounting [mm]	100 x 100
--------------------	-----------

---

## Additional Features

---

Special Characteristics	Ambient light sensor for optimized brightness levels; Auto Contrast; Carbon Footprint Meter; Carbon Savings Meter; ControlSync®; Customize Setting; DICOM simulation; EcoModes; ErgoDesign®: Height adjustable stand (150 mm) with 90° Pivot features; Human Sensor; LED Backlight Technology; Quick release Stand and Handle; USB ver. 3.1 (3 down / 1 up); Versatile and easy installation (VESA standard) with NaViSet and NaViKey; Windows 10 compatible
-------------------------	--

---

Colour Versions	Black Front Bezel, Black Back Cabinet; White Front Bezel, White Back Cabinet
-----------------	--

---

Cable Management	yes
------------------	-----

---

Kensington security slot	yes
--------------------------	-----

---

Plug and Play	DDC2B/2Bi; EDID Standard; VESA DDC/CI
---------------	---------------------------------------

---

Audio	Headphone Jack; Integrated Speakers (1 W + 1 W)
-------	---

---

Adjust Functions	Audio Volume / Lock-Out; Auto Adjust; Brightness; Colour Temperature Control; Contrast; Control Sync; DV Mode; EcoMode; Factory Preset; Fine Adjust (analog); Human Sensing; Intelligent Power Management; Language Select; Monitor Information; NTAA (Non-Touch-Auto-Adjustment); On-Screen-Display (OSD) lock-out; One Touch Recovery; Power-Off Timer; sRGB
Shipping Content	Control Sync Cable; DisplayPort cable; Monitor; Power Cable; Set-up Manual; Setup Guide; USB Cable; USB-C Cable
Safety and Ergonomics	CE; EAC; EnergyStar 8.0; ErP; FCC Class B; Flicker-free; ISO 9241-307 (pixel failure class I); Low Blue Light; PSB; RoHS; TCO 8.0; TCO Edge 2.0; TÜV Ergonomics; TÜV GS; UL/C-UL or CSA
Warranty	3 years warranty incl. backlight; optional 1st to 3rd year 24/7 usage warranty; optional 4th to 5th year warranty extension

## Green Features

Energy Efficiency	Ambient light sensor; Auto brightness; Carbon footprint meter / Carbon savings meter; ECOMode; Energy consumption: 15 kWh/1000 h; Energy efficiency class: D; Human sensor; LED backlight technology
Ecological Materials	Efficient mechanical design for minimised packaging; Minimal use of harmful material
Ecological Standards	ErP compliant; WEEE

\* TCO 8.0

\* TCO Edge 2.0

\* EnergyStar 8.0



TÜV GS



ErP



RoHS



TÜV Ergonomics



TCO 8.0



CE



FCC Class B

This document is © 2025 Sharp NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered

trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 09.10.2025