




Spectrum II
XC




Spectrum II
XLCR



Spectrum II
XATM

Type	Centre loudspeaker 2 way Bass-reflex	On wall loudspeaker 2 way Bass-reflex	Atmos loudspeaker Coaxial 2 way Sealed
Power	80 W RMS / 120 W Peak	80 W RMS / 120 W Peak	50 W RMS / 80 W Peak
Power amplifier	20 - 120 W	20 - 120 W	20 - 80 W
Drive-Units	Tweeter : 1" Dome Mid-woofer : 2 x 4" Cellulose pulp	Tweeter : 1" Dome Mid-woofer : 2 x 4" Cellulose pulp	Tweeter : 3/4" Dome Mid-woofer : 5" Cellulose pulp
Frequency response	55 Hz - 20 kHz (±3dB)	57 Hz - 20 kHz (±3dB)	70 Hz - 20 kHz (±3dB)
Sensitivity	88 dB / 1W / 1m	88 dB / 1W / 1m	88 dB / 1W / 1m
Crossover	2300 Hz - 12 dB / 12 dB	3200 Hz - 12 dB / 12 dB	2200 Hz - 12 dB / 12 dB + Atmos network
Nominal impedance	6 Ω	6 Ω	6 Ω

Dimensions	W395 x H145 x D198 mm	W186 x H660 x D110 mm	W166 x H60-140 x D268 mm
Weight	4,6 kg	6,5 kg	2,8 kg
Finishes	Black, White	Black, White	Black, White



Spectrum II
XSW 8

Type	Active subwoofer Sealed
Power	100 W RMS
Inputs	Stereo RCA
Variable cut off frequency	50 - 150 Hz
Drive-Units	8" Cellulose pulp
Phase	0° / 180°
Frequency response	25 - 200 Hz
Standby	Yes
Auto wake up	Yes
Dimensions	W270 x H270 x D275 mm
Weight	10 kg
Finishes	Black, White