

televic
conference

D-Cerno C SL

D-Cerno Chairman Discussion Unit with Removable Microphone



Description

D-Cerno introduces a new era: an innovator within its market segment. It combines *sleek design with digital signal processing and plug-and-play functionality*.

Stylish, discreet, and unobtrusive with a low profile: the D-Cerno C SL *is at home in any meeting room context*.

The system is completely based on digital signal processing. The result is *crystal-clear sound and excellent intelligibility*. Two cornerstones of any successful meeting.

In a global, interconnected world where communication is crucial, immunity to typical mobile phone interference is simply a must. D-Cerno's shielded microphone eliminates these

disturbances, so delegates can focus on the essence of the meeting.

The system is designed to work out-of-the-box, with hardly any technical expertise required. Wiring is easy: simply connect shielded Cat 5 cables from unit to unit. While connecting, there is no need to worry about the IN and OUT port since the unit detects the direction of the signal flow automatically. It makes cabling errors virtually impossible.

The system has the added benefit of easy extensibility: increasing or decreasing the number of units is a breeze. It makes D-Cerno ideal for rental use.

In comparison with the D-Cerno D SL, the D-Cerno C SL has two additional buttons: *Priority* and *Next-in-line*. The Priority button silences all delegate microphones and allows only the

chairperson to speak. It is possible to precede this function by a chime. The Next-in-line button gives the floor to the next speaker in a waiting list of speakers who requested to speak.

The D-Cerno C SL is compatible with screw-lock D-MIC microphones in 30, 40, 50, or 70 cm.

Benefits

- Contemporary design fits in everywhere
- Superior lifespan
- Plug-and-play approach

Features

- Digital signal processing
- Stylish, unobtrusive, low profile design
- Shielded microphone, immune to mobile phone interference
- High-quality integrated loudspeaker
- Headphone output
- Headphone volume adjustment
- Microphone On/Off button
- Loop-through, daisy-chain cabling
- Patented fail-safe redundancy feature
- Concealed conference bus connections
- Bi-color bar indicator
- Microphone On/Off or Request-to-speak push button with 2 signaling LEDs

Connectivity

- 2 digital bus connections (IN/OUT - interchangeable)
- Headphone connection

TEL152 Headphones **71.04.0154**

- Screw-lock socket to connect a removable microphone:

D-MIC30SL	71.98.0053
D-MIC40SL	71.98.0054
D-MIC50SL	71.98.0055
D-MIC70SL	71.98.0057

- A 2 m patch cable is included with the unit

Certifications

Region	Certification
Europe	CE

Specifications

Mechanical	
Material	PC/ABS
Color	Black
Size (mm)	TBD
Size packed (mm)	TBD
Weight (g)	TBD
Weight packed (g)	TBD
Electrical	
Power Supply	48 DC, over Cat5 cable
Audio quality	16 bit digital
Power consumption	2 W
Frequency response	25 Hz-15,000 Hz (\pm 3 dB)
Headphone	
Impedance	16-150 Ω
Output level	Max 70 mW 32 Ω
Environment	
Operating temperature	5 to 50 $^{\circ}$ C
Humidity	Protection class EP10 Compliant to IEC 60069_2.14

All information copyright **Televic Conference**, 2018. Version 1.0, April 2018

—
 Leo Bekaertlaan 1 · 8870 Izegem · Belgium
 Tel. +32 51 30 30 45
 Fax +32 51 31 06 70
 E-mail: conference@televic.com
 Web: <http://www.televic-conference.com>
Televic reserves the right to change this document without notice.