

Flat Panel Ceiling Lifts—FPLCV2 +R+LM+LOCK

FPLC V2+R+LM+LOCK series of flat panel ceiling lift mechanisms combines rotation and vertical lowering motion, presenting a unique solution for high end, demanding installations!

FPLC V2+R+LM+LOCK models provide swiveling at 90 degrees from ceiling, full vertical lowering motion and rotation ability up to ± 180 degrees (full rotation to both directions)! Optionally they can be equipped with electric tilt ability. Maximum safety is achieved in closed position with the electric safety locking system.



Model	FPLCV2-42-50+R+LM+LOCK	FPLCV2-52-65+R+LM+LOCK
Maximum flat panel dimensions (WxHxD)	$\leq 1280 \times 755 \times 90$ mm	$\leq 1500 \times 925 \times 90$ mm
Maximum load (flat panel+ceiling cover)	45kg	
Lift dimensions (WxHxL)	1610x300x1485mm	1835x300x1650mm
Maximum swiveling angle	90degrees	
Vertical lowering motion	795mm	960mm
Rotation ability	± 180 degrees both ways : 180° CW & 180° CCW	
Mounting flat panel holes pattern up to	800x400mm	800x600mm
Standard color of metallic parts	powder coating in RAL 9005 black or RAL 9016 white	
Power supply	110-230VAC-50/60Hz	
Standard control option	dry contacts control box	
Optional controls	RF or IR remote control, RS 232 or 485 ports	

ALL RIGHTS ARE STRICTLY RESERVED.

REPRODUCTION OR ISSUE TO 3RD PARTIES IN ANY FORM WHATEBVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORIZATION BY UNITECH SYSTEMS
All above information may change by the manufacturer without prior notice or obligation of any kind.