



On one end: USB A - plugs into the old connector on your laptop and carries USB 3.0 signal.

On the other end: USB type C - the new smaller reversible USB plug which supports USB 3.1 signal.

**1m (3.2ft)**

TC 1MUSBCA EU SAP: 4322261 US SAP: 12938689

**2m (6.5ft)**

TC 2MUSBCA EU SAP: 4322262 US SAP: 12938690

**3m (9.8ft)** END OF LIFE

TC 3MUSBCA EU SAP: 4322263 US SAP: 12939451

### SPECIFICATIONS

#### TC 1MUSBCA White USB-C to USB 3.0A Cable 1m (3.2ft)

**SHEATH: PVC, OUTER DIAMETER**

4.0 mm (0.16")

**CONDUCTOR THICKNESS**

22+30 AWG

**BANDWIDTH**

480Mbit/s

**CHARGING CURRENT**

3 A

**COMPLIANCE**

RoHS, CE, FCC

**PACKAGED WEIGHT**

0.03 kg (0.06 lb)

**PRODUCT WEIGHT**

0.023 kg (0.05 lb)

**PACKAGED DIMENSIONS**

150 x 150 x 30 mm (5.91" x 5.91" x 1.18")

**USB 3.0 CABLE**

**NICKEL-PLATED CONNECTORS**

**SUPPORTS ALT MODE WHERE CABLE USED FOR DISPLAYPORT OR HDMI SIGNAL INSTEAD OF USB**

## TC 2MUSBCA White USB-C to USB 3.0A Cable 2m (6.5ft)

---

**SHEATH: PVC, OUTER DIAMETER**

4.0 mm (0.16")

**CONDUCTOR THICKNESS**

22+30 AWG

**BANDWIDTH**

480Mbit/s

**CHARGING CURRENT**

3 A

**COMPLIANCE**

RoHS, CE, FCC

**PACKAGED WEIGHT**

0.07 kg (0.15 lb)

**PRODUCT WEIGHT**

0.063 kg (0.14 lb)

**PACKAGED DIMENSIONS**

150 x 150 x 30 mm (5.91" x 5.91" x 1.18")

**USB 3.0 CABLE****NICKEL-PLATED CONNECTORS**

**SUPPORTS ALT MODE WHERE CABLE USED FOR DISPLAYPORT OR HDMI SIGNAL INSTEAD OF USB**

## TC 3MUSBCA White USB-C to USB 3.0A Cable 3m (9.8ft)

---

**SHEATH: PVC, OUTER DIAMETER**

4.0 mm (0.16")

**CONDUCTOR THICKNESS**

22+30 AWG

**BANDWIDTH**

5Gbps

**CHARGING CURRENT**

3 A

**COMPLIANCE**

RoHS, CE, FCC

**PACKAGED WEIGHT**

0.1 kg (0.22 lb)

**PRODUCT WEIGHT**

0.090 kg (0.20 lb)

**PACKAGED DIMENSIONS**

160 x 160 x 45 mm (6.3" x 6.3" x 1.8")

**USB 3.0 CABLE****NICKEL-PLATED CONNECTORS**

**SUPPORTS ALT MODE WHERE CABLE USED FOR DISPLAYPORT OR HDMI SIGNAL INSTEAD OF USB**