



### 1m (3.2ft) **END OF LIFE**

TC 1MUSBEXT EU SAP: 3265181 US SAP: 12939573

### 2m (6.5ft) **END OF LIFE**

TC 2MUSBEXT EU SAP: 3265182 US SAP: 12939556

### 3m (9.8ft) **END OF LIFE AUGUST 2021**

TC 3MUSBEXT+ EU SAP: 4500879 US SAP: 13041747

### 5m (16.4ft)

TC 5MUSBEXT+ EU SAP: 4500880 US SAP: 13041700

## SPECIFICATIONS

### TC 1MUSBEXT White USB 2.0 Extension Cable 1m (3.2ft)

#### INSULATION

HDPE

#### SHEATH: PVC, OUTER DIAMETER

4.5mm (0.18")

#### CONDUCTOR THICKNESS

28+24AWG

#### BANDWIDTH

480Mbit/s

#### SHEILDING

> 65% coverage braided shield

#### COMPLIANCE

RoHS, CE, FCC

#### PACKAGED WEIGHT

0.04 kg (0.09 lb)

#### PACKAGED DIMENSION

150 x 150 x 30 mm (5.91" x 5.91" x 1.18")

#### HIGH SPEED USB 2.0 CABLE

FERRITE CORES ON BOTH ENDS TO STOP RF INTERFERENCE

GOLD-PLATED CONNECTORS

## TC 2MUSBEXT White USB 2.0 Extension Cable 2m (6.5ft)

---

### INSULATION

HDPE

### SHEATH: PVC, OUTER DIAMETER

4.5mm (0.18")

### CONDUCTOR THICKNESS

28+24AWG

### BANDWIDTH

480Mbit/s

### SHEILDING

> 65% coverage braided shield

### COMPLIANCE

RoHS, CE, FCC

### PACKAGED WEIGHT

0.08 kg (0.18 lb)

### PACKAGED DIMENSION

160 x 160 x 45 mm (6.3" x 6.3" x 1.8")

### HIGH SPEED USB 2.0 CABLE

FERRITE CORES ON BOTH ENDS TO STOP RF INTERFERENCE

GOLD-PLATED CONNECTORS

## TC 3MUSBEXT+ White USB 2.0 Extension Cable 3m (9.8ft) with active booster

---

### BOOSTER HOUSING

48 x 25 mm / 1.9"x 1.0" (length x width)

### INSULATION

HDPE

### SHEATH: PVC, OUTER DIAMETER

4.5mm (0.18")

### CONDUCTOR THICKNESS

28+24AWG

### BANDWIDTH

480Mbit/s

### SHEILDING

> 65% coverage braided shield

### COMPLIANCE

RoHS, CE, FCC

### PACKAGED WEIGHT

0.11 kg (0.24 lb)

### PACKAGED DIMENSION

160 x 160 x 45 mm (6.3" x 6.3" x 1.8")

### HIGH SPEED USB 2.0 CABLE

ACTIVE BOOSTER CIRCUIT USES 5V FROM USB TO MAINTAIN SIGNAL STRENGTH

FERRITE CORES ON BOTH ENDS TO STOP RF INTERFERENCE

GOLD-PLATED CONNECTORS

## TC 5MUSBEXT+ White USB 2.0 Extension Cable 5m (16.4ft) with active booster

---

### BOOSTER HOUSING

48 x 25 mm / 1.9"x 1.0" (length x width)

### INSULATION

HDPE

### SHEATH: PVC, OUTER DIAMETER

4.5mm (0.18")

### CONDUCTOR THICKNESS

28+24AWG

### BANDWIDTH

480Mbit/s

### SHEILDING

> 65% coverage braided shield

### COMPLIANCE

RoHS, CE, FCC

### PACKAGED WEIGHT

0.18 kg (0.40 lb)

### PACKAGED DIMENSION

160 x 160 x 45 mm (6.3" x 6.3" x 1.8")

### LENGTHHIGH SPEED USB 2.0 CABLE

ACTIVE BOOSTER CIRCUIT USES 5V FROM USB TO MAINTAIN SIGNAL STRENGTH

FERRITE CORES ON BOTH ENDS TO STOP RF INTERFERENCE

GOLD-PLATED CONNECTORS