WYRESTORM ENADO™ MINI CONTROL SOLUTION
ENA-MINI-010

KEY FEATURES:

- Provides an intuitive, customizable user interface to control WyreStorm devices and other AV components.
- Web server-based design allows for easy setup, operation, maintenance and management of the system.
- Highly scalable to allow for control of any AV component (WyreStorm or other manufacturer) over the network.
- Multi-platform ie. iOS, Android, Macs and PC control with an unlimited number of user control devices without any licensing costs.
- Wizard-based setup for all connected displays and sources allows for quick setup and template-driven integration with WyreStorm products.

They say good things come in small packages, so why should a control solution be any different? Meet the Enado™ Mini Web Server A/V Control System

A revolution in AV control, the Enado Mini is a small form-factor IP-only control system built on server-based technology; essentially, a small computer system containing the full Enado software suite that can be installed anywhere on a Network in any location to act as a powerful web server user interface for control of virtually any device with Ethernet connectivity by any device with a web browser.

BRING YOUR OWN DEVICE
Control any connected IP device with Enado control software eliminating the need for apps, PC software, drivers or control device configuration with no additional costs for upgrades, updates or licenses, whilst delivering an app-like experience. Compatible with any platform on any web-enabled device from smartphones to tablets to laptops and computers, control devices can be added in seconds with simple QR code and bookmarked set up that's effortlessly client-friendly.

SMART, STREAMLINED SOLUTION WITH INSTANT UPDATES
The removal of IR, RS232 and relay/cc connectivity, helps keep costs low enough for minimal impact on project budget, whilst being smart enough to allow output connection using iTach and Flex devices from Global Cache.

Enado Mini's server-centric design solves a multitude of issues for the installer with system updates instantaneous and free for a control solution that's always on, always accessible and always up to date.

WIZARD-BASED, TEMPLATE-DRIVEN SET UP
Integrates seamlessly with step-by-step wizard-based configuration and 'what you see is what you get' interface editing. Initial setup of the system is made even easier with access to the expansive library of templates for connected devices for unlimited control of all WyreStorm distribution devices over IP while controlling all other sources with Global Cache.

Enado Mini offers IP control of WyreStorm NetworkHD and matrix products, AVR, Blu-ray players, set-top boxes such as SkyHD, TiVo, Virgin, Humax, media players like AppleTV, Roku, Sky Now, XBMC and Kaleidescape as well as games consoles and a growing number of Smart TVs, all over IP with no additional hardware required.

Yes Enado Mini is small, but it packs a serious punch.

IN THE BOX

1 x ENA-MINI-010 Main unit
1 x 5V/2A Power supply
1 x Serial service cable
5 x IP address labels

1 x Quickstart guide (also downloadable from the Enado MINI product page)
NOTE: Full product instructions included internally within the Enado software

SPECIFICATIONS

I/O Connections	1 x LAN
LED	Power LED, Active LED
Power Supply	5V/2A DC, 5.5mm
Power Consumption	1.4 Watts
Control Method	Web; Telnet
System Requirements	Industry Standard CAT5e/6 Cables
Operating Temperature	32°F to 95°F (0°C to 35°C) 10% to 90%, non-condensing
Storage Temperature	-4°F to 140°F (-20°C to 70°C) 10% to 90%, non-condensing
ESD Protection	±8kV (air-gap discharge)
	±4kV (contact discharge)
Surge Protection	Voltage: ±1000 V
Dimension (W x H x D)	141mm × 115mm × 26mm / 5.6" × 4.5" × 1"
Weight	0.42kg / 0.92lbs (without accessories)
Certification	CE, FCC, RoHS