


# USB-C to USBC Cable (1m/3ft) or (2m/6ft)

EXP-CAB-USBC-xM



## Quickstart Guide

 WyreStorm recommends reading through this document in its entirety to become familiar with the product's features prior to starting the installation process.



### In the Box

1x EXP-CAB-USBC-xM Cable

### Wiring and Connections

#### IMPORTANT! Installation Requirements

- Follow the labeling and the diagrams for connection to ensure proper operation.

Audio and Video	
Video Resolution (Max)	1920x1080p @ 240Hz 4096x2160p @60Hz 4:4:4 10bit 4096x2160p @60Hz 4:4:4 12bit
Audio Formats	2ch PCM
Supported Standards	RGB   USB Superspeed   USB Alt-Mode
Communication and Control	
USB	USB 3.2 Gen 2x2   Superspeed 20Gbps
Power	
Power Delivery	20V 5A (100w)
Environmental	
Operating Temperature	14°F ~ 158°F (-10°C ~ 70°C)   0% ~ 85%, non-condensing
Storage Temperature	-40°F ~ 185°F (-40°C ~ 85°C)   0% ~ 85%, non-condensing
Dimensions and Weight	
Length	1m/3ft   2m/6ft
Cable Diameter	0.043kg/.09lbs (1m)   0.066kg/.15lbs (2m)
Regulatory	
Safety and Emission	CE   FCC   RoHS   EAC   RCM

**Note:** WyreStorm reserves the right to change product specification, appearance or dimensions of this product at any time without prior notice.

### Warranty Information

WyreStorm Technologies ProAV Corporation warrants that its products to be free from defects in material and workmanship under normal use for a period of two (2) years from the date of purchase. Refer to the Product Warranty page on [wyrestorm.com](http://wyrestorm.com) for more details on our limited product warranty.

