

Specification Sheet





WyreStorm - Powerful. Reliable. Simple.

Introduction

The FOCUS 200 PRO is a 4K ultra HD Zoom-certified business webcam. Equipped with a 120° wide-angle distortionless lens, it ensures top-of-the-line image quality. It also boasts auto framing, 8x digital zoom, dual Al noise-cancelling mics and App control, ideal for small and medium-sized meeting rooms. Furthermore, Auto-Framing and Presenter Tracking ensures you're always the focus of meetings.

Key Features

- · Captures crystal clear 4K UHD video with automatic color correction and white balance
- Up to 120° ultra-wide angle lens ensures the entire room is in frame
- ePTZ support for Auto-Framing, Presenter Tracking or manual pan, tilt & zoom adjustments
- · Gesture control supported
- · Zoom Certified
- Easily adjusts to fit on top of any computer monitor or display, no matter the size
- · Privacy cover for when the camera is not in use
- Integrated microphone features auto-noise reduction and a 3-meter pickup range
- $\bullet \quad \text{Compatible with popular conference software such as Microsoft Teams and Zoom, Skype and more!}\\$
- Intuitive Focus App software for adjusting video settings and more for all Focus models

In the Box

1x WyreStorm Focus 200 Pro Webcam 1x Privacy Cover 1x USB-C to USB-A Cable

Specifications

Video	
Outputs	1x USB 3.0 Type C Female
	1280x720p @90Hz
Video Resolutions (Max)	1920x1080p @60Hz
	3840x2160p @30Hz*
Output Video Encoding	MJPEG/H.264/H.265/YUY2/NV12 UVC 1.1
Camera and Sensor	
Lens	Fixed
Sensor	CMOS, Effective Pixel: 8.0M
Shutter	1/30s ~ 1/10000s
White Balance	Auto
Backlight Compensation	Supported
DNR (Digital Noise Reduction)	Supported
Auto-Framing	Supported
Presenter Tracking	Supported
Viewing Angle	Diagonal: 120°
Gesture Control	Supported
Power	
Power Supply	USB 5V
Power Consumption	2.5w
Environmental	
Operating Temperature	32°F ~ 104°F (0°C ~ 40°C), 10% ~ 90%, non-condensing
Storage Temperature	$-4^{\circ}F \sim 140^{\circ}F$ (-20°C $\sim +60^{\circ}C$), 10% ~ 90 %, non-condensing
Dimensions and Weight	
Length x Width x Height	140.29mm/5.52in x 73.7mm/2.9in x 62.5mm/2.46in
Weight	0.14kg/0.31lbs
Regulatory	
Safety and Emission	CE FCC RoHS EAC RCM

^{*}For best performance of video capture at 4K a USB 3.0 connection should be used. If a USB 2.0 port is used only 1080p60Hz can be guaranteed. *When using presenter tracking, USB 2.0 can only support 1080p30Hz. Presenter tracking at 4K or 60Hz requires USB 3.0.

Note: WyreStorm reserves the right to change product specification, appearance or dimensions of this product at any time without prior notice.