



# unitech systems



inspiring|solutions

contents

products for projectors

projector mechanisms	page 3-8
projector ceiling lifts	page 3-6
projector wall & table/furniture lifts	page 7
customized projector lifts	page 8

products for flat panels

flat panel mechanisms	page 9-32
flat panel art mechanisms	page 9
flat panel rail mechanisms	page 10
flat panel ceiling lifts	page 11-22
flat panel extension mechanism	page 23
flat panel table/furniture lifts	page 24-30
flat panel mounts	
flat panel wall mounts	page 31
flat panel floor stands	page 32

customized products

customized solutions	page 33-35
anti-vibration 19'' racks	page 33
outdoor lift & screen	page 34
customized products	page 35

Projector Ceiling Lifts

Unitech Systems has developed a wide range of ceiling lift mechanisms for projectors, which is evolving and renewed according to the modern needs of both residential and professional AV applications.



PLCV2 series

PLCV2 series of projector ceiling lift mechanisms is characterized by excellent utility, amazing stability and absolute accuracy in up and down positions. All mechanisms of PLCV2 series are equipped with the unique feature of four (4) heavy duty linear guides that provides maximum stability and safety in motion and absolute accuracy in start and end positions.



Technical details

Model	PLC V2.1	PLC V2.2	PLC V2.3
Projector dimensions (WxHxD)	≤ 680x213x650mm	≤ 505x185x509mm	≤ 440x180x392mm
Maximum load (projector+ceiling cover)	40kg	25kg	20kg
Lift dimensions (WxHxD)	896x374x659mm	796x305x509mm	794x305x392mm
Lift weight	~60kg	~42kg	~32kg
Standard drop distance	720mm	780mm	
Optional drop distance (*)	+385mm	+385mm	
(*): Lift height increase at	410mm	405mm	
Standard color of metallic parts	RAL 9005 black		
Optional RAL color selection	up on request		
Power supply	wire control at 230VAC-50/60Hz		
Optional controls	RF remote control, dry contacts		

## Projector Ceiling Lifts



### PLCV5 series

PLCV5 series of projector ceiling lift mechanisms is characterized by its low profile and its wide range of models, thus providing flexibility in installation and solutions of excellent utility in demanding applications.



### Technical details

Model	PLC V5.1	PLC V5.2	PLC V5.3	PLC V5.4
Projector dimensions (WxD)	≤ 470x440mm	≤ 420x440mm	≤ 555x596mm	≤ 580x707mm
Maximum load (projector+ceiling cover)	20kg			35kg
Lift dimensions (WxD)	635x440mm	526x440mm	690x596mm	720x850mm
Lift height	71+projector height for max.projector depth <345mm 105+projector height for max.projector depth >345mm			85mm+proj.height
Lift weight	~19kg	~15kg	~30kg	~44kg
Standard drop distance	200mm		300mm	500mm
Optional extra drop distance (*)	maximum 2 times of +200mm each		maximum 2 times of +300mm each	maximum 2 times of +500mm each
(*): Lift height increase at	+42mm each time		+40mm each time	+46mm each time
Standard color of metallic parts	RAL 9005 black			
Optional RAL color selection	up on request			
Power supply	wire control at 230VAC-50/60Hz			
Optional controls	RF remote control, dry contacts			

## Projector Ceiling Lifts

EMEA  
**INAVATION**  
AWARDS 2014  
TECHNOLOGY FINALIST



### PLCV6 series

**The slimmest projector ceiling lift is a reality!**

Required inner ceiling depth only **1.5cm** + projector height\*!

Easy to install, with high quality technical specifications and consistent with Unitech Systems' philosophy for reliable and firm constructions, PLCV6 series is the ultimate solution for slim ceiling applications.

### Technical details

Model	PLC V6.1
Projector dimensions (WxHxD)	530x645mm
Maximum load (projector+ceiling cover)	20kg
Lift dimensions (WxHxD)	787x854mm
Mounting area dimensions (W&D) in mm	482x430mm
Lift Height	1.5cm + projector height*
Standard drop distance	300mm
Projector sliding mounting tray	✓
Cable management system	✓
Standard color of metallic parts	RAL 9005 black
Optional RAL color selection	up on request
Power supply	230VAC-50/60Hz
Optional controls	RF remote control, dry contacts

\*for projectors' height >135mm



## Heavy Duty Projector Ceiling Lifts

Unitech Systems standardizes the heavy duty projector ceiling lifts required in **professional applications**, for maximum load capacity up to 100kg and introduces the new series PLCS-V2.

Keeping the high standards in utility, quality and stability, this new line incorporates 3 sets of articulated scissor elements, providing stability in motion and 4 metal wires for maximum safety. The lift is equipped with projector mount which provides independent leveling adjustments for tilt and pitch and with speed motion controller which enables soft start/stop of motion function. The articulated scissors are equipped with cable holding points, in order to facilitate the cable routing and their secure motion with the lift.

Silent in operation and with standard drop distance up to 3m, the PCLS-V2 line is the reliable solution for professional applications!



### Technical details

Model	PLCS-1500V2	PLCS-2000V2	PLCS-2500V2	PLCS-3000V2
Space inside carriage for projector (WxL)	655x950mm			
Maximum load capacity (projector+ceiling cover)	100kg			
Lift dimensions (WxD)	885x1000mm			
Net vertical drop down length	1500mm	2000mm	2500mm	3000mm
Minimum required inner ceiling depth, with projector mount providing angle position adjustments	401mm +projector height	438mm +projector height	475mm +projector height	512mm +projector height
Tilt/pitch adjustment	±8.5degrees / ±6.5degrees			
Standard color of metallic parts	powder coating in RAL 9005 black or RAL 9016 white			
Power supply	230VAC-50/60Hz			
Standard control option	dry contacts control box			
Optional controls	RF remote control, RS 232 or 485 ports			

## Projector Wall & Table/Furniture Lifts

Unitech Systems designs and produces special mechanisms for wall or furniture applications, giving architectural and designing solutions beyond the ordinary.



Standard product range of Projector Wall & Table Lifts:

### Technical details


Model	PLWV V2	PLWH LM V2	PLT V3.1
Projector dimensions (WxD)	≤ 510x450mm	≤ 530x500mm	≤ 530x185x503mm
Maximum load (projector+wall cover)	20kg	25kg	20kg
Lift dimensions (WxD)	660x628mm	595x541mm	675x365mm
Lift height/depth	<ul style="list-style-type: none"><li>• minimum D:302mm for projectors up to 175mm height</li><li>• D:127mm+projector height, for projectors over 175mm height</li></ul>	H: 125mm+projector height	H: 1030mm
Rising distance	-	-	600mm
Opening/swiveling angle	up to 90degrees	-	90degrees
Horizontal linear motion distance	-	400mm	-
Standard color of metallic parts	RAL 9005 black		
Optional RAL color selection	up on request		
Power supply	wire control at 230VAC-50/60Hz		
Optional controls	RF remote control, dry contacts		

# Projector Customized lifts

Driven by our customers' requests and needs, the designing team of Unitech Systems designs and develops a large number of customized products



Heavy duty ceiling lifts for big size projectors in customized drop down lengths.



Hydraulic lifts for vertical rising of loads up to 200kg.

# Flat panel Art cover mechanisms

Designers and art lovers will find the ideal solution for covering the TV set in the most artistic way! FPArt mechanisms can be installed on any wall surface and combined with the wall mount of the clients' selection, they provide a unique art expression, while characterized by high utility.



FPArt V4 series\*



## Technical details

Model	FPArt V4 30-40	FPArt V4 42-50	FPArt V4 52-60
Maximum flat panel dimensions (WxHxD)	≤ 1025x640x90mm	≤ 1280x755x90mm	≤ 1480x900x90mm
Art mechanism dimensions (WxHxD)	1202x805x130mm	1460x920x130mm	1660x1065x130mm
Art mechanism weight	~21kg	~25kg	~30kg
Dimensions of wooden frame (WxHxD)	1245x870x20mm	1500x985x20mm	1700x1130x20mm
Standard color of metallic parts	RAL 9005 black		
Power supply	wire control at 230VAC-50/60Hz		
Optional controls	RF remote control, dry contacts		

\*: includes painting and standard wooden frame, does not include flat panel wall mount.



# Flat panel Rail mechanism



## FPCRM V4 series

The new Rail ceiling system, series FPCRMV4, designed by Unitech Systems, is an an innovating flexible product that allows viewing your flat panel TV in more than one areas of your home or office, while providing a minimal aesthetic result. It has been designed to meet the modern needs of home and office environment, providing features of motion in horizontal, vertical axis and rotation, in combination with a low profile aluminum rail, easy to hide or combine with other features of the ceiling.

The new systems' unique element is the elegant aluminum ceiling rail, accompanied by a series of accessories, which provides the following features:

- ✓ Horizontal run length up to 12 meters, in any intermediate length desired by the client
- ✓ Manual or automated linear motion
- ✓ Manual or automated full rotation of suspended mount up to 300degrees
- ✓ Suspension of AV equipment by
  - Fixed height arm mount, in two (2) standard heights or
  - Mounting flanges according to standard or customized vesa mounting
- ✓ Invisible cable routing inside the aluminum ceiling rail, in cable chain
- ✓ Maximum weight of suspended equipment
  - 50kg in fixed arm mount
  - 35kg in lift mechanism
- ✓ Elegant design
- ✓ Coloring of aluminum rail in four (4) anodized colors: aluminum, black, cooper, inox
- ✓ Smooth motion
- ✓ Safety in application
- ✓ Silent motion

## Optional features

- Flat panel mounts with vesa patterns from 200x200mm up to 600x400mm
- Customized mounts
- Vertical lift mechanisms with elevation run length up to 1000mm



# Flat panel Ceiling Lifts



## FPLC V3 series

FPLC V3 series of flat panel ceiling lift mechanisms is characterized by excellent utility and stability providing solutions to every situation!

FPLC V3 series of lifts includes models that when in closed position, the flat panel faces up towards the ceiling and models that when in closed position, the flat panel faces down towards the floor.



## Technical details

Model	FPLC V3-700U*	FPLC V3-700D*	FPLC V3-800U*	FPLC V3-800D*
Maximum flat panel dimensions (WxHxD)	≤ 960x680x115mm	≤ 960x680x115mm	≤ 1310x790x105mm	≤ 1310x765x100mm
Maximum load (flat panel+ceiling cover)	35kg		45kg	
Lift dimensions (WxHxD)	1230x275x1000mm	1230x275x1000mm	1615x275x1100mm	1615x275x1100mm
Maximum swiveling angle	95degrees	90degrees	95degrees	90degrees
Lift weight	~63kg		~75kg	
Vertical linear motion up to	700mm		800mm	
Mounting flat panel hole pattern up to	800x400mm		825x600mm	
Cable management system	✓			
Standard color of metallic parts	RAL 9005 black & RAL 9016 white			
Power supply	wire control at 230VAC-50/60Hz with dry contacts			
Optional controls	RF remote control			

U\*: flat panel facing Up

D\*: flat panel facing Down

# Flat panel Ceiling Lifts



## FPLC V4 series

FPLC V4 series of flat panel ceiling lift mechanisms is one of the simplest lifts, easy to install and use, that is characterized as a highly cost efficient solution! FPLC V4 series' smooth operation and high utility makes it an excellent and smart choice!



## Technical details

Model	FPLC V4-32	FPLC V4-42	FPLC V4-52
Maximum flat panel dimensions (WxHxD)	≤ 823x450x90mm	≤ 1045x650x90mm	≤ 1250x750x90mm
Maximum load (flat panel+ceiling cover)	35kg	40kg	40kg
Lift dimensions (WxHxD)	1100x238x500mm	1320x238x700mm	1450x238x820mm
Lift weight	~36kg	~45kg	~65kg
Maximum swiveling angle	110degrees	110degrees	110degrees
Mounting flat panel hole pattern up to	600x300mm	800x400mm	800x400mm
Standard color of metallic parts	RAL 9005 black matte & RAL 9016 white		
Power supply	wire control at 230VAC-50/60Hz		
Optional controls	RF remote control, dry contacts		

# Flat Panel Ceiling Lifts



## FPLCV6-55

Unitech Systems presents the ULTRA slim flat panel ceiling lift, FPLCV6-55! A yet again innovating solution requiring only 9.5cm inside false ceiling, designed by Unitech Systems, gives answers to applications with limited inner false ceiling depth for TV sets up to 55".

## Technical details

Model	FPLC V6-55
Maximum flat panel dimensions (WxHxD)	≤ 1245x740x65mm
Maximum load (flat panel+ceiling cover)	30kg
Lift dimensions (WxHxL), excluding control box	1430x95x935mm
Swiveling angle	100degrees
Lift weight	~40kg
Mounting flat panel holes pattern up to	600x400mm
Standard color of metallic parts	powder coating in RAL 9005 black or RAL 9016 white
Power supply	230VAC-50/60Hz
Standard control option	wall switch
Optional controls	RF remote control, dry contacts control box, RS 232 or 485 ports



## Flat panel Ceiling Lifts

Specialized series of flat panel lifts series are included in Unitech Systems' constantly expanding and evolving product range.

Characterized by unique features and making smart ideas a reality, the lift mechanisms of Unitech Systems guarantee that in their range you will find the right product for your needs!

Easy to install and reliable in operation, Unitech Systems' flat panel lifts provide solutions to professionals!



### FPLC V2 Slim series

FPLC V2 Slim series of flat panel ceiling lift mechanisms is characterized by excellent utility, slim profile and unique features. Elegant and silent, this popular series of lifts is constantly enriched by new models!

FPLC V2 Slim provides simple swiveling at 110 degrees from ceiling and minimum ceiling depth required at just 160mm!



### Technical details

Model	FPLC V2 Slim 30-40	FPLC V2 Slim 42-50	FPLC V2 Slim 52-60
Maximum flat panel dimensions (WxHxD)	≤ 1025x620x90mm	≤ 1280x755x90mm	≤ 1480x900x90mm
Maximum load (flat panel+ceiling cover)	30kg	35kg	45kg
Lift dimensions (WxHxD) excluding control box	1455x160x780mm	1712x160x916mm	1912x160x1045mm
Lift weight	~60kg	~72kg	~84kg
Maximum swiveling angle	110degrees		
Mounting flat panel hole pattern up to	600x400mm	800x400mm	800x600mm
Standard color of metallic parts	powder coating in RAL 9005 black or RAL 9016 white		
Power supply	110-230VAC-50/60Hz		
Standard control option	dry contacts control box		
Optional controls	RF remote control, RS 232 or 485 ports		

## Flat panel Ceiling Lifts for XL size TVs

### FPLC V2 series

The FPLC V2 series of flat panel ceiling lift mechanisms for large TV sizes >65". Elegant and silent, this heavy duty series of lifts provides safety and utility, while concealing large TV sets inside ceiling structure .

FPLC V2 series with simple swiveling at 100 degrees from ceiling and minimum ceiling depth required at 270mm, is also equipped with safety locking system in closed position.



### Technical details

Model	FPLC V2-75	FPLC V2-85
Maximum flat panel dimensions (WxHxD)	≤ 1700x1000x120mm	≤ 1930x1100x120mm
Maximum load (flat panel+ceiling cover)	65kg	
Lift dimensions (WxHxD) excluding control box	2050x270x1420mm	2280x270x1520mm
Maximum swiveling angle	100degrees	
Mounting flat panel holes pattern up to	800x600mm	
Safety locking system in closed position	√	
Standard color of metallic parts	powder coating in RAL 9005 black or RAL 9016 white	
Power supply	110-230VAC-50/60Hz	
Standard control option	dry contacts control box	
Optional controls	RF remote control, RS 232 or 485 ports	





FPLC V2 Slim+R series

FPLC V2 Slim+R series of flat panel ceiling lift mechanisms completes the series of elegant and slim ceiling mechanism with new models that comprise rotation ability and excellent utility!

Giving ideal solutions in most demanding applications of reduce space, (e.g. marine or vessel applications), FPLC V2 Slim+R series impress both users and integrators!

FPLC V2 Slim+R models provide swiveling at 90 degrees from ceiling and rotation ability up to ±180degrees (full rotation to both directions).

The model suitable for flat panels up to 60"-65" is also equipped with an electric safety locking system in closed position, to ensure maximum security of application.



Technical details

Model	FPLCV2Slim30-40+R	FPLCV2Slim42-50+R	FPLCV2Slim52-60+R+LOCK
Maximum flat panel dimensions (WxHxD)	≤ 1025x620x90mm	≤ 1280x755x90mm	≤ 1480x900x90mm
Maximum load (flat panel+ceiling cover)	25kg	30kg	35kg
Lift dimensions (WxHxD) excluding control box	1330x220x1125mm	1615x220x1300mm	1820x220x1525mm
Maximum swiveling angle	90degrees		
Rotation ability (CW & CCW)	±180degrees both ways : 180° CW & 180° CCW		
Mounting flat panel holes pattern up to	600x400mm	800x400mm	800x600mm
Standard color of metallic parts	powder coating in RAL 9005 black or RAL 9016 white		
Power supply	110-230VAC-50/60Hz		
Standard control option	dry contacts control box		
Optional controls	RF remote control, RS 232 or 485 ports		

Flat panel Ceiling Lifts

FPLC V2 SLIM+R+TILT series

The FPLC V2 SLIM+R+TILT series of flat panel ceiling lifts with full rotation, can be also equipped with flat panel tilt ability, up to 30degrees!

This optimum solution, provides maximum utility with its full rotation and best viewing angle for different positions in the same room. For example, viewing from table top or from bed or sofa demands different viewing angles. This is easily solved by the variety of viewing angles that FPLCV2+R+TILT series offers to the end user!



Technical details

Model	FPLC V2 Slim 30-40+R+TILT	FPLC V2 Slim 42-50+R+TILT	FPLC V2 Slim 52-60+R+TILT+LOCK
Maximum flat panel dimensions (WxHxD)	≤ 1025x620x90mm	≤ 1280x755x90mm	≤ 1480x900x90mm
Maximum load (flat panel+ceiling cover)	25kg	30kg	35kg
Lift dimensions (WxHxD) excluding control box	1330x220x1125mm	1615x220x1300mm	1820x250x1525mm
Swiveling angle	90degrees		
Rotation ability (CW & CCW)	±180degrees both ways : 180° CW & 180° CCW		
Flat panel electric tilt ability	up to 30degrees		
Mounting flat panel holes pattern up to	600x400mm	800x400mm	800x600mm
Standard color of metallic parts	powder coating in RAL 9005 black or RAL 9016 white		
Power supply	110-230VAC-50/60Hz		
Standard control option	dry contacts control box		
Optional controls	RF remote control, RS 232 or 485 ports		



# Flat panel Ceiling Lifts

## FPLC V2 +LM series


The FPLC V2 +LM series of flat panel ceiling lift mechanisms offers vertical lowering motion, for applications with increased floor-ceiling distance.

Maximum safety is achieved in closed position with the electric safety locking system. Its silent operation and smooth motion make this series an elegant and reliable solution!



Technical details

Model	FPLCV2-42-50+LM+LOCK	FPLCV2-52-60+LM+LOCK
Maximum flat panel dimensions (WxHxD)	≤ 1280x755x90mm	≤ 1480x900x90mm
Maximum load (flat panel+ceiling cover)	45kg	
Lift dimensions (WxHxD) excluding control box	1600x260x1023mm	800x260x1160mm
Vertical lowering distance up to	310mm	460mm
Mounting flat panel holes pattern up to	800x400mm	800x600mm
Standard color of metallic parts	powder coating in RAL 9005 black or RAL 9016 white	
Power supply	110-230VAC-50/60Hz	
Standard control option	dry contacts control box	
Optional controls	RF remote control, RS 232 or 485 ports	



# Flat Panel Ceiling Lifts

## FPLCV2 –85+ILM+LOCK

FPLC V2+LM series of flat panel ceiling lift mechanisms offers vertical lowering motion, for applications with increased floor-ceiling distance. The addition of FPLCV2-85+LM+LOCK model covers plus size TV sets.

Maximum safety is achieved in closed position with the electric safety locking system. Its silent operation and smooth motion make this series an elegant and reliable solution!



Technical details

Model	FPLCV2-85+LM+LOCK
Maximum flat panel dimensions (WxHxD)	≤ 1930x1100x90mm
Maximum load (flat panel+ceiling cover)	75kg
Lift dimensions (WxHxD)	2360x300x1560mm
Vertical lowering distance up to	655mm
Mounting TV hole pattern (vesa)	800x400mm
Standard color of metallic parts	powder coating in RAL 9005 black or RAL 9016 white
Power supply	110-230VAC-50/60Hz
Standard control option	dry contacts control box
Optional controls	RF remote control, RS 232 or 485 ports





## Flat panel Ceiling Lifts

### FPLC V2 +R+LM+LOCK series

The FPLC V2 +R+LM+LOCK series of flat panel ceiling lift mechanisms combines rotation and vertical lowering motion, presenting a unique solution for high end, demanding installations! FPLC V2 +R+LM+LOCK models provide swiveling at 90 degrees from ceiling, full vertical lowering motion and rotation ability up to ±180degrees (full rotation to both directions)! Optionally they can be equipped with electric tilt ability. Maximum safety is achieved in closed position with the electric safety locking system.



Technical details

Model	FPLCV2-42-50+R+LM+LOCK	FPLCV2-52-65+R+LM+LOCK
Maximum flat panel dimensions (WxHxD)	≤ 1280x755x90mm	≤ 1500x925x90mm
Maximum load (flat panel+ceiling cover)	45kg	
Lift dimensions (WxHxD) excluding control box	1610x300x1485mm	1835x300x1650mm
Maximum swiveling angle	90degrees	
Vertical lowering motion	795mm	960mm
Rotation ability	±180degrees both ways : 180° CW & 180° CCW	
Mounting flat panel holes pattern up to	800x400mm	800x600mm
Standard color of metallic parts	powder coating in RAL 9005 black or RAL 9016 white	
Power supply	110-230VAC-50/60Hz	
Standard control option	dry contacts control box	
Optional controls	RF remote control, RS 232 or 485 ports	



## Flat panel Ceiling Lifts for XL size TVs

### FPLC V2-90+R+LM+LOCK model

Sensitive to the changes in market needs, Unitech Systems transforms the customized solutions for big TVs in a new standard model of TV ceiling lift: the new FPLCV2+R+LM+LOCK-90, suitable for TVs between 75"-90". Silent, safe & ready to install, this new heavy duty ceiling lift, offers a complete set of functions:

- ✓ vertical lowering motion
- ✓ bi-directional rotation ±180°
- ✓ ensuring maximum safety in closed position
- ✓ optional electric tilt ability up to 20degrees for the TV

The lift's solid & firm construction provides maximum duration in time & safety in installation, in addition to its excellent utility!



INAVATION AWARDS  
TECHNOLOGY FINALIST 2016

Technical details

Model	FPLCV2-90+R+LM+LOCK
Maximum flat panel dimensions (WxHxD)	≤ 2060x1215x120mm
Maximum load (flat panel+ceiling cover)	TV weight ≤ 65kg ceiling cover weight ≤ 30kg
Lift dimensions (WxHxD)	2801x395x2215mm
Maximum swiveling angle	90degrees
Mounting TV hole pattern (vesa)	adjustable
TV bi-directional rotation	± 180degrees
Standard color of metallic parts	powder coating in RAL 9005 black or RAL 9016 white
Power supply	110-230VAC-50/60Hz
Standard control option	dry contacts control box
Optional controls	RF remote control, RS 232 or 485 ports
Optional features	Electric tilt feature, for tilt up to 20degrees



## Flat panel Wall/Ceiling Lifts

A yet innovating series of products, combining highly reliable operation, easy installation and safety in use!

The wall series of Unitech Systems' lifts can be easily installed on wall or from ceiling, multiplying the provided solutions to interior designers' needs.




**FPLW V1 series**

FPLW V1 series of wall or ceiling mounted lifts guarantee optimal utility with their smooth vertical motion.

**Technical details**

Model	FPLW V1-600	FPLW V1-700	FPLW V1-800	FPLW V1-900
Vertical run length up to	600mm	700mm	800mm	900mm
Maximum load	35kg	40kg	45kg	50kg
Lift dimensions (WxHxD)	893x606x115mm	893x706x115mm	893x806x115mm	893x906x115mm
Lift weight	~25kg	~30kg	~36kg	~42kg
Mounting flat panel hole patterns	820x485mm	820x585mm	820x735mm	820x735mm
Cable management system	✓			
Standard color of metallic parts	RAL 9005 black			
Power supply	wire control at 230VAC-50/60Hz			
Optional controls	RF remote control, dry contacts			



## Panel Mechanism & Flat panel Floor/Furniture Lift

New ideas, driven from clients' requests!

The new panel extension mechanism, PA-WLH series, designed by Unitech Systems, provides horizontal extension from wall or furniture surface level up to 300mm, giving the ability for your flat panel to appear from inside the wall!

Combined with FPLTS flat panel floor/furniture lifts, with FPTLSR flat panel floor/furniture lift with side rotation, or with FPLWV1 series of vertical lifts, PA-WLH series provide complete disappearing of your flat panel with no compromises in their utility!





## Flat panel Table/Furniture Lifts

Reliable operation and easy installation are some of the features that make Unitech Systems' table/furniture lift mechanisms the best choice!



### FPLT S V2 series

FPLT S V2 series of flat panel table/furniture lift mechanisms is characterized by slim profile and smooth motion. Including a big number of models, it covers all sizes of flat panels on a best cost basis!



### Technical details

Model	FPLT S V2-500	FPLT S V2-600	FPLT S V2-700	FPLT S V2-800	FPLT S V2-900	FPLT S V2-1100
Maximum elevation height (flat panel height + furniture cover pitch)	≤ 460mm	≤ 560mm	≤ 660mm	≤ 760mm	≤ 860mm	≤ 1050mm
Maximum load (flat panel+furniture cover)	25kg	35kg	35kg	45kg	45kg	45kg
Lift dimensions (HxD)	510x90mm	610x90mm	710x90mm	810x90mm	910x90mm	1110X90mm
Lift width (including cable chain)	676mm	810mm	810mm	857mm	857mm	857mm
Lift weight	21kg	22kg	24kg	27kg	30kg	40kg
Mounting flat panel hole pattern up to	600x350mm	620x400mm	620x540mm	720x610mm	720x750mm	720X820mm
Cable management system	✓					
Standard color of metallic parts	RAL 9005 black					
Power supply	wire control at 230VAC-50/60Hz					
Optional controls	RF remote control, dry contacts					

## Flat Panel Table/Floor/Furniture Lifts

The most reliable solution for demanding applications involving big size or heavy weight TV sets, is Unitech Systems' heavy duty FPLT-HD-V1 series of floor/furniture lifts!



### FPLT-HD-V1 series

FPLT-HD-V1 series of flat panel pop-up lifts is characterized by firm construction, easy installation and smooth motion. Easily adapted in specific demands, it can cover most client needs!

### Technical details

Model	FPLT-HD-V1-1100	FPLT-HD-V1-1200	FPLT-HD-V1-1200
Lift dimensions (WxD)	725x270mm		
Vertical motion up to (includes TV height+furniture cover pitch+spare air above and below)	800mm	1000mm	1200mm
Lift height (/raised height)	1070mm (/1870mm)	1270mm (/2270mm)	1470mm (/2670mm)
Maximum load capacity (≥ flat panel + furniture cover)	80kg		
Cable management system	✓		
Standard color of metallic parts	powder coating in RAL 9005 black		
Power supply	wire control at 230VAC-50/60Hz with dry contacts		
Standard control option	Dry contacts multi pin connector		
Optional controls	RF remote control, RS 232 or 485 ports		



# Flat panel Table/Furniture Lifts



**FPLTSR V5.3 side rotation**

FPLTSR V5.3 series is completed with a group of models that combines vertical elevation with side rotation (left or right to be determined at order confirmation) providing a full coverage of clients' needs.

**Technical details**

Model	FPLTSR V5.3-700	FPLTSR V5.3-800	FPLTSR V5.3-900
Maximum elevation height (flat panel height + furniture cover pitch)	≤ 650mm	≤ 750mm	≤ 850mm
Maximum load (flat panel+furniture cover)	35kg	35kg	45kg
Automatic side rotation up to	90degrees		
Lift dimensions (HxD)	725x240mm	825x240mm	925x240mm
Mounting flat panel hole pattern up to	600x400mm	800x400mm	
Cable management system	✓		
Standard color of metallic parts	RAL 9005 black		
Power supply	wire control at 230VAC-50/60Hz with dry contacts		
Optional controls	RF remote control		



# Flat panel Table/Furniture lifts



**FPLTR V3 series**

FPLTR V3 series provides vertical rising from inside furniture and after ful rising is completed, the flat panel has the ability to fully rotated up until 300degrees and backwards.

Smooth motion, excellent stability, firm construction and ease of application are the main characteristics of FPLTRV3 series.

**Technical details**

Model	FPLTR V3-600	FPLTR V3-700	FPLTR V3-800	FPLTR V3-900
Maximum elevation height (including furniture cover pitch)	≤ 600mm	≤ 700mm	≤ 800mm	≤910mm
Maximum load (flat panel+furniture cover)	25kg	30kg	35kg	35kg
Automatic side rotation up to	300degrees			
Maximum flat panel dimensions (WxHxD)	1130x550x110mm	1230x650x110mm	1330x750x110mm	1500x850x110mm
Lift dimensions (WxHxD)	1315x800x260mm	1415x900x260mm	1515x1000x260mm	1700x1120x260mm
Cable management system	✓			
Standard color of metallic parts	RAL 9005 black			
Power supply	wire control at 230VAC-50/60Hz with dry contacts			
Optional controls	RF remote control, RS 232 or 485 ports			





# Flat panel Table/Furniture Lifts

## FPLT V2 series

The unique FPLT V2 series of at panel table/furniture lift mechanisms is the innovating answer of Unitech Systems to its client needs!

Characterized by heavy duty and highly reliable construction, FPLT V2 series of mechanism bring new solutions in interior design needs. With the use of an FPLT V2 lift, a simple coffee table or a couch will be converted to a smart TV solution!



**FPLT V2**  
FPLT V2 models with simple swiveling up to 100 degrees:



Technical details

Model	FPLT V2 30-40	FPLT V2 42-50	FPLT V2 52-60
Maximum flat panel dimensions (WxHxD)	≤ 1025x620x100mm	≤ 1280x756x100mm	≤ 1480x900x100mm
Maximum load (flat panel+ceiling cover)	35kg	40kg	45kg
Lift dimensions (WxHxD)	1366x250x804mm	1621x250x940mm	1821x250x1084mm
Maximum swiveling angle	100degrees		
Mounting flat panel hole pattern up to	600x400mm	800x400mm	800x600mm
Cable management system	✓		
Standard color of metallic parts	RAL 9005 black		
Power supply	110-230VAC-50/60Hz with dry contacts		
Optional controls	RF remote control, RS 232 or 485 ports		



# Flat panel Table/Furniture Lifts

**FPLT V2-500 (350)**  
FPLT V2-500 (350) models with simple swiveling up to 90 degrees and vertical elevation up to 500mm:



Technical details

Model	FPLT V2-350 30-40	FPLT V2-500 42-50	FPLT V2-500 52-60
Maximum flat panel dimensions (WxHxD)	≤ 1025x620x100mm	≤ 1280x756x100mm	≤ 1480x900x100mm
Maximum load (flat panel+ceiling cover)	35kg	40kg	45kg
Lift dimensions (WxHxD)	1366x250x804mm	1621x250x940mm	1821x250x1084mm
Maximum swiveling angle	90degrees		
Vertical elevation up to	350mm	500mm	
Mounting flat panel hole pattern up to	600x400mm	800x400mm	800x600mm
Cable management system	✓		
Standard color of metallic parts	RAL 9005 black		
Power supply	110-230VAC-50/60Hz with dry contacts		
Optional controls	RF remote control, RS 232 or 485 ports		

# Flat panel Table/Furniture Lifts



## FPLT V6 series

FPLT V6 series of monitor table/furniture lift mechanisms is an easily installed smart solution for embedding monitors up to 30" inside furniture.



## Technical details

Model	FPLT V6-500	FPLT V6-600
Maximum flat panel dimensions (WxHxD)	≤ 515x430x73mm	≤ 665x530x73mm
Maximum elevation height (flat panel height + furniture cover pitch)	≤ 430mm	≤ 530mm
Maximum load (flat panel+furniture cover)	10kg	20kg
Lift dimensions (WxHxD)	650x550x157mm	800x650x157mm
Mounting flat panel hole patterns	50x50mm, 75x75mm, 100x100mm & 200x200mm & 300x200mm	
Cable management system	✓	
Standard color of metallic parts	RAL 9005 black	
Power supply	wire control at 230VAC-50/60Hz	
Optional controls	RF remote control, dry contacts	

# Flat Panel Wall Mounts

Unitech Systems is constantly enriching its mounting solutions, providing both manual and electric wall mounts for flat panels, with unique features and excellent utility!  
Mounts that allow you to view your TV from the room next door!



## Technical details

Model	FPWMRTV1.4-400	FPWMRTV1.4-500	FPWMRTV1.4-600	FPWMR-MV7	FPWMR-MV8
Number of rotation axis	2			1	2
Arm bracket swiveling angle	up to 165 degrees			-	
Flat panel swiveling angle	up to 180 degrees			one way swivelling, up to 90 degrees	articulated swiveling up to 75 degrees, for maximim TV width 1550mm
Maximum load capacity	50kg	50kg	40kg	80kg	50kg
Mounting flat panel hole pattern up to	670x440mm			100x100mm - 600x400mm	200x200mm 300x300mm 400x400mm
Manual extension from wall	965mm	1165mm	1350mm	-	
Cable management system	✓				
Standard color of metallic parts	RAL 9005 black				
Operation / Power supply	manual			dry contacts / 230VAC-50/60Hz	dry contacts / 230VAC-50/60Hz
Optional controls	-			RF remote control, RS232/485	



## Flat panel Floor Stands

### FPFS series

Unitech Systems has a big variety of flat panel floor stand models, giving answers to various professional or home environment needs. Each model brings added value to the end user, with unique features such as telescopic height adjustment at any intermediate point with no step by step restriction, easy change of set up, use of elegant stainless steel vertical brackets, optional features, etc.

With modular set up, various optional accessories (shelves, camera brackets, wheels, etc) and multiple universal mounts for flat panels with different features, the FPFS models designed by Unitech Systems give elegant solutions for all kind of applications.



## Anti-Vibration Rack systems



### Features

- The innovating design of this series, allows the firm installment of the racks, protecting at the same time the equipment mounted in them by reducing at minimum the vibrations transmitted from the rack's body to the equipment. This is achieved with the use of double rack module (box in the box) and the use of anti-shock accessories.
- The AntiVibration features can be adjusted according to the weight of the equipment installed in the rack, providing this way the maximum resistance in vibration transmission possible.
- The AntiVibration 19" Rack series is ideal for use in multi vibration environment, such as ships and general marine applications, automobiles, airplanes, mobile operation centers, etc, where vibrations can be destructive for sensitive equipment (e.g. servers, etc).
- Standard dimensions for this series of racks include: 15U, 27U, 32U and 42U, with nominal depth 600 & 1000mm.
- AntiVibration 19" Racks can be assembled in banks and can be accompanied by several accessories like doors, side covers, roof ventilation, telescopic shelves, etc.
- The doors of AntiVibration 19" Rack series are designed in such a way so that the user can have visual contact with the inside of the racks.
- An innovating feature of the new AntiVibration 19" rack series, exclusively designed by **Unitech Systems**, is the air fans on the front door, which allow the equipment that need air flow from their front side to be adequately ventilated.
- The new AntiVibration 19" rack is accompanied by a digital temperature controller at the front side, which displays the temperature inside the rack and has two independent signal controls that can be used for alarm, secondary ventilation system start, etc.

### Accessories

- Blank panels (1U, 2U, 3U, 4U and 6U)
- Shelves 19" (1U, 2U, 3U and 4U)
- Telescopic shelves 19" (1U, 2U and 3U) with telescopic run 400mm and 700mm.
- Drawers 19" (1U, 2U and 3U)
- Telescopic shelf for 17" monitor and mini keyboard.
- Set of wheels (turned and with break).
- Various accessories like multi sockets, screws, grills of cables, etc.



## Customized Solutions

The strong designing team of Unitech Systems provides its clients the ability to realize their dream plans!



Outdoor lift & screen mechanism for private cinema theater.



## Customized Solutions

Specialization and experience provide Unitech Systems' clients with solutions for every need, for professional or home applications!







unitech  
systems

[www.unitech-systems.eu](http://www.unitech-systems.eu)

[info@unitech-systems.eu](mailto:info@unitech-systems.eu)

+30 210 6086270